



Film Capacitors

Metallized Polypropylene Film Capacitors (MKP)

Series/Type: B32656S
Date: February 2010

Snubber (wound)
Typical applications

- IGBT
- Snubbing

Climatic

- Max. operating temperature: 110 °C
- Climatic category (IEC 60068-1): 55/100/56

Construction

- Dielectric: polypropylene (PP)
- Wound capacitor technology with internal series connection
- Plastic case (UL 94 V-0)
- Epoxy resin sealing (UL 94 V-0)

Features

- High pulse strength and high contact reliability
- Very low inductance

Terminals



- Strap terminals, tinned copper or brass (max. torque 10 Nm)

Marking

Manufacturer's logo, ordering code, style (MKP)
rated capacitance (coded), cap. tolerance (code letter),
rated DC voltage, date of manufacture (coded)


Delivery mode

Bulk (untaped)


Dimensional drawings
T1 (code no. 561)

T2 (code no. 562)


Dimensional drawings (continued)


T3 (code no. 563)




T4 (code no. 564)




T5 (code no. 565)



T6 (code no. 566)






B32656S


Snubber (wound)

T7 (code no. 577)



Overview of available types

Type	B32656S				
V _R (V DC)	850	1000	1250	1600	2000
V _{RMS} (V AC)	450	480	500	750	800
C _R (nF)					
47					
68					
100					
120					
150					
220					
270					
330					
390					
470					
560					
680					
820					
1000					
1200					
1500					
1800					
2200					
2700					
3300					


B32656S
Snubber (wound)
Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
850	450	220	$12.0 \times 22.5 \times 42.0$	5	10.0	B32656S8224+563	T3	224
		220	$12.0 \times 22.5 \times 42.0$	5	10.0	B32656S8224+564	T4	384
		270	$12.0 \times 22.5 \times 42.0$	6	9.0	B32656S8274+563	T3	224
		270	$12.0 \times 22.5 \times 42.0$	6	9.0	B32656S8274+564	T4	384
		330	$12.0 \times 22.5 \times 42.0$	6	9.0	B32656S8334+563	T3	224
		330	$12.0 \times 22.5 \times 42.0$	6	9.0	B32656S8334+564	T4	384
		390	$12.0 \times 22.5 \times 42.0$	7	8.0	B32656S8394+563	T3	224
		390	$12.0 \times 22.5 \times 42.0$	7	8.0	B32656S8394+564	T4	384
		470	$12.0 \times 22.5 \times 42.0$	8	8.0	B32656S8474+563	T3	224
		470	$12.0 \times 22.5 \times 42.0$	8	8.0	B32656S8474+564	T4	384
		560	$14.0 \times 25.0 \times 42.0$	8	7.0	B32656S8564+563	T3	168
		560	$14.0 \times 25.0 \times 42.0$	8	7.0	B32656S8564+564	T4	288
		560	$14.0 \times 25.0 \times 42.0$	8	7.0	B32656S8564+565	T5	288
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+561	T1	192
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+562	T2	192
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+563	T3	144
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+564	T4	192
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+565	T5	192
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+566	T6	192
		680	$16.0 \times 28.5 \times 42.0$	9	6.0	B32656S8684+577	T7	180
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+561	T1	192
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+562	T2	192
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+563	T3	144
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+564	T4	192
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+565	T5	192
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+566	T6	192
		820	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S8824+577	T7	180

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$

B32656S	
Snubber (wound)	

	
MKP	

Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz m Ω	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
850	450	1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+561	T1	168
		1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+562	T2	168
		1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+563	T3	144
		1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+564	T4	128
		1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+565	T5	128
		1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+566	T6	168
		1000	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S8105+577	T7	156
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+561	T1	168
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+562	T2	168
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+563	T3	144
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+564	T4	128
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+565	T5	128
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+566	T6	168
		1200	$18.0 \times 32.5 \times 42.0$	11	5.0	B32656S8125+577	T7	156
		1500	$31.0 \times 26.5 \times 43.6$	13	5.0	B32656S8155+561	T1	128
		1500	$31.0 \times 26.5 \times 43.6$	13	5.0	B32656S8155+562	T2	128
		1500	$31.0 \times 26.5 \times 43.6$	13	5.0	B32656S8155+563	T3	72
		1500	$31.0 \times 26.5 \times 43.6$	13	5.0	B32656S8155+566	T6	128
		1500	$31.0 \times 26.5 \times 43.6$	13	5.0	B32656S8155+577	T7	84
		1800	$28.0 \times 37.0 \times 42.0$	15	4.5	B32656S8185+561	T1	108
		1800	$28.0 \times 37.0 \times 42.0$	15	4.5	B32656S8185+562	T2	108
		1800	$28.0 \times 37.0 \times 42.0$	15	4.5	B32656S8185+563	T3	96
		1800	$28.0 \times 37.0 \times 42.0$	15	4.5	B32656S8185+566	T6	108
		1800	$28.0 \times 37.0 \times 42.0$	15	4.5	B32656S8185+577	T7	96
		2200	$30.0 \times 45.0 \times 42.0$	17	3.5	B32656S8225+561	T1	48
		2200	$30.0 \times 45.0 \times 42.0$	17	3.5	B32656S8225+562	T2	48
		2200	$30.0 \times 45.0 \times 42.0$	17	3.5	B32656S8225+563	T3	96
		2200	$30.0 \times 45.0 \times 42.0$	17	3.5	B32656S8225+566	T6	48
		2200	$30.0 \times 45.0 \times 42.0$	17	3.5	B32656S8225+577	T7	96

MOQ = Minimum Order Quantity, consisting of 4 packing units.


Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$


B32656S
Snubber (wound)
Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
850	450	2700	$30.0 \times 45.0 \times 42.0$	20	3.0	B32656S8275+561	T1	48
		2700	$30.0 \times 45.0 \times 42.0$	20	3.0	B32656S8275+562	T2	48
		2700	$30.0 \times 45.0 \times 42.0$	20	3.0	B32656S8275+563	T3	96
		2700	$30.0 \times 45.0 \times 42.0$	20	3.0	B32656S8275+566	T6	48
		2700	$30.0 \times 45.0 \times 42.0$	20	3.0	B32656S8275+577	T7	96
		3300	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S8335+561	T1	84
		3300	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S8335+562	T2	84
		3300	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S8335+563	T3	64
		3300	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S8335+566	T6	84
		3300	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S8335+577	T7	84
1000	480	220	$12.0 \times 22.5 \times 42.0$	6	10.0	B32656S0224+563	T3	224
		220	$12.0 \times 22.5 \times 42.0$	6	10.0	B32656S0224+564	T4	384
		270	$12.0 \times 22.5 \times 42.0$	7	9.0	B32656S0274+563	T3	224
		270	$12.0 \times 22.5 \times 42.0$	7	9.0	B32656S0274+564	T4	384
		330	$14.0 \times 25.0 \times 42.0$	7	9.0	B32656S0334+563	T3	168
		330	$14.0 \times 25.0 \times 42.0$	7	9.0	B32656S0334+564	T4	288
		330	$14.0 \times 25.0 \times 42.0$	7	9.0	B32656S0334+565	T5	288
		390	$14.0 \times 25.0 \times 42.0$	8	8.0	B32656S0394+563	T3	168
		390	$14.0 \times 25.0 \times 42.0$	8	8.0	B32656S0394+564	T4	288
		390	$14.0 \times 25.0 \times 42.0$	8	8.0	B32656S0394+565	T5	288
		470	$14.0 \times 25.0 \times 42.0$	9	8.0	B32656S0474+563	T3	168
		470	$14.0 \times 25.0 \times 42.0$	9	8.0	B32656S0474+564	T4	288
		470	$14.0 \times 25.0 \times 42.0$	9	8.0	B32656S0474+565	T5	288
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+561	T1	192
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+562	T2	192
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+563	T3	144
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+564	T4	192
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+565	T5	192
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+566	T6	192
		560	$16.0 \times 28.5 \times 42.0$	9	7.0	B32656S0564+577	T7	180

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$

B32656S	
Snubber (wound)	

	
MKP	

Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
1000	480	680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+561	T1	192
		680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+562	T2	192
		680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+563	T3	144
		680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+564	T4	192
		680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+565	T5	192
		680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+566	T6	192
		680	$16.0 \times 28.5 \times 42.0$	10	6.0	B32656S0684+577	T7	180
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+561	T1	168
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+562	T2	168
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+563	T3	144
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+564	T4	128
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+565	T5	128
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+566	T6	168
		820	$18.0 \times 32.5 \times 42.0$	11	6.0	B32656S0824+577	T7	156
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+561	T1	96
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+562	T2	96
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+563	T3	104
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+564	T4	96
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+565	T5	96
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+566	T6	96
		1000	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S0105+577	T7	144
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+561	T1	96
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+562	T2	96
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+563	T3	104
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+564	T4	96
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+565	T5	96
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+566	T6	96
		1200	$20.0 \times 39.5 \times 42.0$	13	5.0	B32656S0125+577	T7	144

MOQ = Minimum Order Quantity, consisting of 4 packing units.


Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$


B32656S
Snubber (wound)
Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
1000	480	1500	$30.0 \times 45.0 \times 42.0$	15	5.0	B32656S0155+561	T1	48
		1500	$30.0 \times 45.0 \times 42.0$	15	5.0	B32656S0155+562	T2	48
		1500	$30.0 \times 45.0 \times 42.0$	15	5.0	B32656S0155+563	T3	96
		1500	$30.0 \times 45.0 \times 42.0$	15	5.0	B32656S0155+566	T6	48
		1500	$30.0 \times 45.0 \times 42.0$	15	5.0	B32656S0155+577	T7	96
		1800	$30.0 \times 45.0 \times 42.0$	16	4.5	B32656S0185+561	T1	48
		1800	$30.0 \times 45.0 \times 42.0$	16	4.5	B32656S0185+562	T2	48
		1800	$30.0 \times 45.0 \times 42.0$	16	4.5	B32656S0185+563	T3	96
		1800	$30.0 \times 45.0 \times 42.0$	16	4.5	B32656S0185+566	T6	48
		1800	$30.0 \times 45.0 \times 42.0$	16	4.5	B32656S0185+577	T7	96
		2200	$30.0 \times 45.0 \times 42.0$	19	3.5	B32656S0225+561	T1	48
		2200	$30.0 \times 45.0 \times 42.0$	19	3.5	B32656S0225+562	T2	48
		2200	$30.0 \times 45.0 \times 42.0$	19	3.5	B32656S0225+563	T3	96
		2200	$30.0 \times 45.0 \times 42.0$	19	3.5	B32656S0225+566	T6	48
		2200	$30.0 \times 45.0 \times 42.0$	19	3.5	B32656S0225+577	T7	96
		2700	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S0275+561	T1	84
		2700	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S0275+562	T2	84
		2700	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S0275+563	T3	64
		2700	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S0275+566	T6	84
		2700	$33.0 \times 48.0 \times 43.0$	23	2.5	B32656S0275+577	T7	84
1250	500	120	$12.0 \times 22.5 \times 42.0$	5	15.0	B32656S7124+563	T3	224
		120	$12.0 \times 22.5 \times 42.0$	5	15.0	B32656S7124+564	T4	384
		150	$12.0 \times 22.5 \times 42.0$	6	15.0	B32656S7154+563	T3	224
		150	$12.0 \times 22.5 \times 42.0$	6	15.0	B32656S7154+564	T4	384
		220	$14.0 \times 25.0 \times 42.0$	8	10.0	B32656S7224+563	T3	168
		220	$14.0 \times 25.0 \times 42.0$	8	10.0	B32656S7224+564	T4	288
		220	$14.0 \times 25.0 \times 42.0$	8	10.0	B32656S7224+565	T5	288
		270	$14.0 \times 25.0 \times 42.0$	8	9.0	B32656S7274+563	T3	168
		270	$14.0 \times 25.0 \times 42.0$	8	9.0	B32656S7274+564	T4	288
		270	$14.0 \times 25.0 \times 42.0$	8	9.0	B32656S7274+565	T5	288

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$

B32656S	
Snubber (wound)	

	
MKP	

Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
1250	500	330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+561	T1	192
		330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+562	T2	192
		330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+563	T3	144
		330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+564	T4	192
		330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+565	T5	192
		330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+566	T6	192
		330	$16.0 \times 28.5 \times 42.0$	8	9.0	B32656S7334+577	T7	180
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+561	T1	168
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+562	T2	168
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+563	T3	144
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+564	T4	128
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+565	T5	128
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+566	T6	168
		390	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7394+577	T7	156
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+561	T1	168
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+562	T2	168
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+563	T3	144
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+564	T4	128
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+565	T5	128
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+566	T6	168
		470	$18.0 \times 32.5 \times 42.0$	9	8.0	B32656S7474+577	T7	156
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+561	T1	96
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+562	T2	96
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+563	T3	104
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+564	T4	96
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+565	T5	96
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+566	T6	96
		560	$20.0 \times 39.5 \times 42.0$	10	7.0	B32656S7564+577	T7	144

MOQ = Minimum Order Quantity, consisting of 4 packing units.


Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$


B32656S
Snubber (wound)
Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
1250	500	680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+561	T1	96
		680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+562	T2	96
		680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+563	T3	104
		680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+564	T4	96
		680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+565	T5	96
		680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+566	T6	96
		680	$20.0 \times 39.5 \times 42.0$	12	6.0	B32656S7684+577	T7	144
		820	$28.0 \times 37.0 \times 42.0$	13	6.0	B32656S7824+561	T1	108
		820	$28.0 \times 37.0 \times 42.0$	13	6.0	B32656S7824+562	T2	108
		820	$28.0 \times 37.0 \times 42.0$	13	6.0	B32656S7824+563	T3	72
		820	$28.0 \times 37.0 \times 42.0$	13	6.0	B32656S7824+566	T6	108
		820	$28.0 \times 37.0 \times 42.0$	13	6.0	B32656S7824+577	T7	96
		1000	$28.0 \times 37.0 \times 42.0$	15	6.0	B32656S7105+561	T1	108
		1000	$28.0 \times 37.0 \times 42.0$	15	6.0	B32656S7105+562	T2	108
		1000	$28.0 \times 37.0 \times 42.0$	15	6.0	B32656S7105+563	T3	72
		1000	$28.0 \times 37.0 \times 42.0$	15	6.0	B32656S7105+566	T6	108
		1000	$28.0 \times 37.0 \times 42.0$	15	6.0	B32656S7105+577	T7	96
		1200	$30.0 \times 45.0 \times 42.0$	16	5.0	B32656S7125+561	T1	48
		1200	$30.0 \times 45.0 \times 42.0$	16	5.0	B32656S7125+562	T2	48
		1200	$30.0 \times 45.0 \times 42.0$	16	5.0	B32656S7125+563	T3	72
		1200	$30.0 \times 45.0 \times 42.0$	16	5.0	B32656S7125+566	T6	48
		1200	$30.0 \times 45.0 \times 42.0$	16	5.0	B32656S7125+577	T7	96
		1500	$30.0 \times 45.0 \times 42.0$	18	4.0	B32656S7155+561	T1	48
		1500	$30.0 \times 45.0 \times 42.0$	18	4.0	B32656S7155+562	T2	48
		1500	$30.0 \times 45.0 \times 42.0$	18	4.0	B32656S7155+563	T3	72
		1500	$30.0 \times 45.0 \times 42.0$	18	4.0	B32656S7155+566	T6	48
		1500	$30.0 \times 45.0 \times 42.0$	18	4.0	B32656S7155+577	T7	96
		1800	$33.0 \times 48.0 \times 43.0$	22	3.0	B32656S7185+561	T1	84
		1800	$33.0 \times 48.0 \times 43.0$	22	3.0	B32656S7185+562	T2	84
		1800	$33.0 \times 48.0 \times 43.0$	22	3.0	B32656S7185+563	T3	64
		1800	$33.0 \times 48.0 \times 43.0$	22	3.0	B32656S7185+566	T6	84
		1800	$33.0 \times 48.0 \times 43.0$	22	3.0	B32656S7185+577	T7	84

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$

		B32656S
		Snubber (wound)

	
MKP	

Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
1600	750	68	$12.0 \times 22.5 \times 42.0$	5	25.0	B32656S1683+563	T3	224
		68	$12.0 \times 22.5 \times 42.0$	5	25.0	B32656S1683+564	T4	384
		100	$12.0 \times 22.5 \times 42.0$	6	20.0	B32656S1104+563	T3	224
		100	$12.0 \times 22.5 \times 42.0$	6	20.0	B32656S1104+564	T4	384
		120	$14.0 \times 25.0 \times 42.0$	6	15.0	B32656S1124+563	T3	168
		120	$14.0 \times 25.0 \times 42.0$	6	15.0	B32656S1124+564	T4	288
		120	$14.0 \times 25.0 \times 42.0$	6	15.0	B32656S1124+565	T5	288
		150	$14.0 \times 25.0 \times 42.0$	7	15.0	B32656S1154+563	T3	168
		150	$14.0 \times 25.0 \times 42.0$	7	15.0	B32656S1154+564	T4	288
		150	$14.0 \times 25.0 \times 42.0$	7	15.0	B32656S1154+565	T5	288
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+561	T1	192
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+562	T2	192
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+563	T3	144
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+564	T4	192
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+565	T5	192
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+566	T6	192
		220	$16.0 \times 28.5 \times 42.0$	9	10.0	B32656S1224+577	T7	180
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+561	T1	168
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+562	T2	168
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+563	T3	144
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+564	T4	128
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+565	T5	128
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+566	T6	168
		270	$18.0 \times 32.5 \times 42.0$	10	9.0	B32656S1274+577	T7	156
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+561	T1	96
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+562	T2	96
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+563	T3	104
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+564	T4	96
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+565	T5	96
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+566	T6	96
		330	$20.0 \times 39.5 \times 42.0$	12	9.0	B32656S1334+577	T7	144

MOQ = Minimum Order Quantity, consisting of 4 packing units.


Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$


B32656S
Snubber (wound)
Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
1600	750	390	$28.0 \times 37.0 \times 42.0$	13	8.0	B32656S1394+561	T1	108
		390	$28.0 \times 37.0 \times 42.0$	13	8.0	B32656S1394+562	T2	108
		390	$28.0 \times 37.0 \times 42.0$	13	8.0	B32656S1394+563	T3	72
		390	$28.0 \times 37.0 \times 42.0$	13	8.0	B32656S1394+566	T6	108
		390	$28.0 \times 37.0 \times 42.0$	13	8.0	B32656S1394+577	T7	96
		470	$28.0 \times 37.0 \times 42.0$	14	8.0	B32656S1474+561	T1	108
		470	$28.0 \times 37.0 \times 42.0$	14	8.0	B32656S1474+562	T2	108
		470	$28.0 \times 37.0 \times 42.0$	14	8.0	B32656S1474+563	T3	72
		470	$28.0 \times 37.0 \times 42.0$	14	8.0	B32656S1474+566	T6	108
		470	$28.0 \times 37.0 \times 42.0$	14	8.0	B32656S1474+577	T7	96
		560	$30.0 \times 45.0 \times 42.0$	15	7.0	B32656S1564+561	T1	48
		560	$30.0 \times 45.0 \times 42.0$	15	7.0	B32656S1564+562	T2	48
		560	$30.0 \times 45.0 \times 42.0$	15	7.0	B32656S1564+563	T3	72
		560	$30.0 \times 45.0 \times 42.0$	15	7.0	B32656S1564+566	T6	48
		560	$30.0 \times 45.0 \times 42.0$	15	7.0	B32656S1564+577	T7	96
		680	$30.0 \times 45.0 \times 42.0$	17	6.0	B32656S1684+561	T1	48
		680	$30.0 \times 45.0 \times 42.0$	17	6.0	B32656S1684+562	T2	48
		680	$30.0 \times 45.0 \times 42.0$	17	6.0	B32656S1684+563	T3	72
		680	$30.0 \times 45.0 \times 42.0$	17	6.0	B32656S1684+566	T6	48
		680	$30.0 \times 45.0 \times 42.0$	17	6.0	B32656S1684+577	T7	96
		820	$33.0 \times 48.0 \times 43.0$	20	4.5	B32656S1824+561	T1	84
		820	$33.0 \times 48.0 \times 43.0$	20	4.5	B32656S1824+562	T2	84
		820	$33.0 \times 48.0 \times 43.0$	20	4.5	B32656S1824+563	T3	64
		820	$33.0 \times 48.0 \times 43.0$	20	4.5	B32656S1824+566	T6	84
		820	$33.0 \times 48.0 \times 43.0$	20	4.5	B32656S1824+577	T7	84

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$

		B32656S
		Snubber (wound)

	
MKP	

Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz m Ω	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
2000	800	47	12.0 × 22.5 × 42.0	5	35.0	B32656S2473+563	T3	224
		47	12.0 × 22.5 × 42.0	5	35.0	B32656S2473+564	T4	384
		68	14.0 × 25.0 × 42.0	6	25.0	B32656S2683+563	T3	192
		68	14.0 × 25.0 × 42.0	6	25.0	B32656S2683+564	T4	288
		68	14.0 × 25.0 × 42.0	6	25.0	B32656S2683+565	T5	288
		100	14.0 × 25.0 × 42.0	7	20.0	B32656S2104+563	T3	192
		100	14.0 × 25.0 × 42.0	7	20.0	B32656S2104+564	T4	288
		100	14.0 × 25.0 × 42.0	7	20.0	B32656S2104+565	T5	288
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+561	T1	192
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+562	T2	192
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+563	T3	144
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+564	T4	192
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+565	T5	192
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+566	T6	192
		120	16.0 × 28.5 × 42.0	7	15.0	B32656S2124+577	T7	180
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+561	T1	168
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+562	T2	168
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+563	T3	160
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+564	T4	192
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+565	T5	192
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+566	T6	168
		150	18.0 × 32.5 × 42.0	9	15.0	B32656S2154+577	T7	156
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+561	T1	96
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+562	T2	96
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+563	T3	104
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+564	T4	96
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+565	T5	96
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+566	T6	96
		220	20.0 × 39.5 × 42.0	12	10.0	B32656S2224+577	T7	144

MOQ = Minimum Order Quantity, consisting of 4 packing units.


Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$


B32656S
Snubber (wound)
Electrical specifications, ordering codes and packing units

V_R	V_{RMS} $f \leq 1 \text{ kHz}$	C_R	Max. dimensions $w \times h \times l$ mm	I_{RMS} 100 kHz A	ESR 100 kHz $m\Omega$	Ordering code (composition see below)	Ter- minal	pcs./ MOQ
V DC	V AC	nF						
2000	800	270	$28.0 \times 37.0 \times 42.0$	13	9.0	B32656S2274+561	T1	108
		270	$28.0 \times 37.0 \times 42.0$	13	9.0	B32656S2274+562	T2	108
		270	$28.0 \times 37.0 \times 42.0$	13	9.0	B32656S2274+563	T3	72
		270	$28.0 \times 37.0 \times 42.0$	13	9.0	B32656S2274+566	T6	108
		270	$28.0 \times 37.0 \times 42.0$	13	9.0	B32656S2274+577	T7	96
		330	$28.0 \times 37.0 \times 42.0$	14	9.0	B32656S2334+561	T1	108
		330	$28.0 \times 37.0 \times 42.0$	14	9.0	B32656S2334+562	T2	108
		330	$28.0 \times 37.0 \times 42.0$	14	9.0	B32656S2334+563	T3	72
		330	$28.0 \times 37.0 \times 42.0$	14	9.0	B32656S2334+566	T6	108
		330	$28.0 \times 37.0 \times 42.0$	14	9.0	B32656S2334+577	T7	96
		390	$30.0 \times 45.0 \times 42.0$	15	8.0	B32656S2394+561	T1	48
		390	$30.0 \times 45.0 \times 42.0$	15	8.0	B32656S2394+562	T2	48
		390	$30.0 \times 45.0 \times 42.0$	15	8.0	B32656S2394+563	T3	72
		390	$30.0 \times 45.0 \times 42.0$	15	8.0	B32656S2394+566	T6	48
		390	$30.0 \times 45.0 \times 42.0$	15	8.0	B32656S2394+577	T7	96
		470	$30.0 \times 45.0 \times 42.0$	17	8.0	B32656S2474+561	T1	48
		470	$30.0 \times 45.0 \times 42.0$	17	8.0	B32656S2474+562	T2	48
		470	$30.0 \times 45.0 \times 42.0$	17	8.0	B32656S2474+563	T3	72
		470	$30.0 \times 45.0 \times 42.0$	17	8.0	B32656S2474+566	T6	48
		470	$30.0 \times 45.0 \times 42.0$	17	8.0	B32656S2474+577	T7	96
		560	$33.0 \times 48.0 \times 43.0$	20	6.5	B32656S2564+561	T1	84
		560	$33.0 \times 48.0 \times 43.0$	20	6.5	B32656S2564+562	T2	84
		560	$33.0 \times 48.0 \times 43.0$	20	6.5	B32656S2564+563	T3	64
		560	$33.0 \times 48.0 \times 43.0$	20	6.5	B32656S2564+566	T6	84
		560	$33.0 \times 48.0 \times 43.0$	20	6.5	B32656S2564+577	T7	84

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code


+ = Capacitance tolerance code:

K = $\pm 10\%$

J = $\pm 5\%$

Technical data

Operating temperature range	Max. operating temperature $T_{op,max}$ +110 °C Upper category temperature T_{max} +100 °C Lower category temperature T_{min} -55 °C Rated temperature T_R +85 °C			
Dissipation factor $\tan \delta$ (in 10^{-3}) at 20 °C (upper limit values)	at	$C_R \leq 0.1 \mu F$	$0.1 \mu F < C_R \leq 1 \mu F$	$C_R > 1 \mu F$
	1 kHz	—	0.5	0.5
	10 kHz	—	0.8	1.5
	100 kHz	5.0	—	—
Insulation resistance R_{ins} or time constant $\tau = C_R \cdot R_{ins}$ at 20 °C, rel. humidity $\leq 65\%$ (minimum as-delivered values)	$C_R \leq 0.33 \mu F$ 100 G Ω		$C_R > 0.33 \mu F$ 30000 s	
DC test voltage	$1.6 \cdot V_R$, 2 s			
Category voltage V_C (continuous operation with V_{DC} or V_{AC} at $f \leq 1$ kHz)	T_A (°C) $T_A \leq 85$ $85 < T_A \leq 100$	DC voltage derating $V_C = V_R$ $V_C = V_R \cdot (165 - T_A)/80$	AC voltage derating $V_{C,RMS} = V_{RMS}$ $V_{C,RMS} = V_{RMS} \cdot (165 - T_A)/80$	
Operating voltage V_{op} for short operating periods (V_{DC} or V_{AC} at $f \leq 1$ kHz)	T_A (°C) $T_A \leq 85$ $85 < T_A \leq 100$	DC voltage (max. hours) $V_{op} = 1.25 \cdot V_C$ (2000 h) $V_{op} = 1.25 \cdot V_C$ (1000 h)	AC voltage (max. hours) $V_{op} = 1.0 \cdot V_{C,RMS}$ (2000 h) $V_{op} = 1.0 \cdot V_{C,RMS}$ (1000 h)	
Damp heat test Limit values after damp heat test	56 days/40 °C/93% relative humidity Capacitance change $ \Delta C/C $ $\leq 3\%$ Dissipation factor change $\Delta \tan \delta$ $\leq 0.5 \cdot 10^{-3}$ (at 1 kHz) $\leq 1.0 \cdot 10^{-3}$ (at 10 kHz) Insulation resistance R_{ins} $\geq 50\%$ of minimum or time constant $\tau = C_R \cdot R_{ins}$ as-delivered values			
Reliability: Failure rate λ Service life t_{SL}	1 fit ($\leq 1 \cdot 10^{-9}/h$) at $0.5 \cdot V_R$, 40 °C 200 000 h at $1.0 \cdot V_R$, 85 °C For conversion to other operating conditions and temperatures, refer to chapter "Quality, 2 Reliability".			
Failure criteria: Total failure Failure due to variation of parameters	Short circuit or open circuit Capacitance change $ \Delta C/C $ $> 10\%$ Dissipation factor $\tan \delta$ $> 4 \cdot$ upper limit value Insulation resistance R_{ins} $< 1500 M\Omega$ ($C_R \leq 0.33 \mu F$) or time constant $\tau = C_R \cdot R_{ins}$ < 500 s ($C_R > 0.33 \mu F$)			



B32656S

Snubber (wound)

Pulse handling capability

"dV/dt" represents the maximum permissible voltage change per unit of time for non-sinusoidal voltages, expressed in V/μs.

"k₀" represents the maximum permissible pulse characteristic of the waveform applied to the capacitor, expressed in V²/μs.

Note:


The values of dV/dt and k₀ provided below must not be exceeded in order to avoid damaging the capacitor.


dV/dt and k₀ values

V _R (V DC)	V _{RMS} (V AC)	dV/dt in V/μs	k ₀ in V ² /μs
850	450	400	680 000
1000	480	450	900 000
1250	500	500	1 250 000
1600	750	600	1 920 000
2000	800	700	2 800 000

Impedance Z versus frequency f

(typical values)







Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ \text{C}$)

For $T_A > 90^\circ \text{C}$, please refer to "General technical information", section 3.2.3.


850 V DC/450 V AC




1000 V DC/480 V AC




1250 V DC/500 V AC



1600 V DC/750 V AC






B32656S


Snubber (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ\text{C}$)

For $T_A > 90^\circ\text{C}$, please refer to "General technical information", section 3.2.3.

2000 V DC/800 V AC





Mounting guidelines

1 Soldering

1.1 Solderability of leads

The solderability of terminal leads is tested to IEC 60068-2-20, test Ta, method 1.

Before a solderability test is carried out, terminals are subjected to accelerated ageing (to IEC 60068-2-2, test Ba: 4 h exposure to dry heat at 155 °C). Since the ageing temperature is far higher than the upper category temperature of the capacitors, the terminal wires should be cut off from the capacitor before the ageing procedure to prevent the solderability being impaired by the products of any capacitor decomposition that might occur.


Solder bath temperature	235 ±5 °C
Soldering time	2.0 ±0.5 s
Immersion depth	2.0 +0/-0.5 mm from capacitor body or seating plane
Evaluation criteria:	
Visual inspection	Wetting of wire surface by new solder ≥90%, free-flowing solder

1.2 Resistance to soldering heat

Resistance to soldering heat is tested to IEC 60068-2-20, test Tb, method 1A.


Conditions:

Series	Solder bath temperature	Soldering time
MKT boxed (except 2.5 × 6.5 × 7.2 mm) coated uncoated (lead spacing > 10 mm)	260 ±5 °C	10 ±1 s
MFP		
MKP (lead spacing > 7.5 mm)		
MKT boxed (case 2.5 × 6.5 × 7.2 mm)		5 ±1 s
MKP (lead spacing ≤ 7.5 mm)		< 4 s
MKT uncoated (lead spacing ≤ 10 mm) insulated (B32559)		recommended soldering profile for MKT uncoated (lead spacing ≤ 10 mm) and insulated (B32559)




B32656S

Snubber (wound)



Immersion depth	2.0 +0/−0.5 mm from capacitor body or seating plane
Shield	Heat-absorbing board, (1.5 ±0.5) mm thick, between capacitor body and liquid solder
Evaluation criteria:	
Visual inspection	No visible damage
$\Delta C/C_0$	2% for MKT/MKP/MFP 5% for EMI suppression capacitors
$\tan \delta$	As specified in sectional specification



1.3 General notes on soldering

Permissible heat exposure loads on film capacitors are primarily characterized by the upper category temperature $T_{\max}$. Long exposure to temperatures above this type-related temperature limit can lead to changes in the plastic dielectric and thus change irreversibly a capacitor's electrical characteristics. For short exposures (as in practical soldering processes) the heat load (and thus the possible effects on a capacitor) will also depend on other factors like:

- Pre-heating temperature and time
- Forced cooling immediately after soldering
- Terminal characteristics:
 - diameter, length, thermal resistance, special configurations (e.g. crimping)
- Height of capacitor above solder bath
- Shadowing by neighboring components
- Additional heating due to heat dissipation by neighboring components
- Use of solder-resist coatings

The overheating associated with some of these factors can usually be reduced by suitable countermeasures. For example, if a pre-heating step cannot be avoided, an additional or reinforced cooling process may possibly have to be included.


EPCOS recommends the following conditions:

- Pre-heating with a maximum temperature of 110 °C
- Temperature inside the capacitor should not exceed the following limits:
 - MKP/MFP 110 °C
 - MKT 160 °C
- When SMD components are used together with leaded ones, the leaded film capacitors should not pass into the SMD adhesive curing oven. The leaded components should be assembled after the SMD curing step.
- Leaded film capacitors are not suitable for reflow soldering.

Uncoated capacitors

For uncoated MKT capacitors with lead spacings ≤ 10 mm (B32560/B32561) the following measures are recommended:

- pre-heating to not more than 110 °C in the preheater phase
- rapid cooling after soldering



B32656S

Snubber (wound)

2 Cleaning

To determine whether the following solvents, often used to remove flux residues and other substances, are suitable for the capacitors described, refer to the table below:

Type	Ethanol, isopropanol, n-propanol	n-propanol-water mixtures, water with surface tension-reducing tensides (neutral)	Solvent from table A (see next page)	Solvent from table B (see next page)
MKT (uncoated)	Suitable	Unsuitable	In part suitable	Unsuitable
MKT, MKP, MFP (coated/boxed)		Suitable	Suitable	

Even when suitable solvents are used, a reversible change of the electrical characteristics may occur in uncoated capacitors immediately after they are washed. Thus it is always recommended to dry the components (e.g. 4 h at 70 °C) before they are subjected to subsequent electrical testing.

Table A


Manufacturers' designations for trifluoro-trichloro-ethane-based cleaning solvents (selection)

Trifluoro-trichloro-ethane	Mixtures of trifluoro-trichloro-ethane with ethanol and isopropanol	Manufacturer
Freon TF	Freon TE 35; Freon TP 35; Freon TES	Du Pont
Frigen 113 TR	Frigen 113 TR-E; Frigen 113 TR-P; Frigen TR-E 35	Hoechst
Arklone P	Arklone A; Arklone L; Arklone K	ICI
Kaltron 113 MDR	Kaltron 113 MDA; Kaltron 113 MDI; Kaltron 113 MDI 35	Kali-Chemie
Flugene 113	Flugene 113 E; Flugene 113 IPA	Rhone-Progil

Table B (worldwide banned substances)

Manufacturers' designations for unsuitable cleaning solvents (selection)

Mixtures of chlorinated hydrocarbons and ketones with fluorated hydrocarbons	Manufacturer
Freon TMC; Freon TA; Freon TC	Du Pont
Arklone E	ICI
Kaltron 113 MDD; Kaltron 113 MDK	Kali-Chemie
Flugene 113 CM	Rhone-Progil



3 Embedding of capacitors in finished assemblies

In many applications, finished circuit assemblies are embedded in plastic resins. In this case, both chemical and thermal influences of the embedding ("potting") and curing processes must be taken into account.

Our experience has shown that the following potting materials can be recommended: non-flexible epoxy resins with acid-anhydride hardeners; chemically inert, non-conducting fillers; maximum curing temperature of 100 °C.

Caution:

Consult us first if you wish to embed uncoated types!



B32656S

Snubber (wound)


Cautions and warnings

- Do not exceed the upper category temperature (UCT).
- Do not apply any mechanical stress to the capacitor terminals.
- Avoid any compressive, tensile or flexural stress.
- Do not move the capacitor after it has been soldered to the PC board.
- Do not pick up the PC board by the soldered capacitor.
- Do not place the capacitor on a PC board whose PTH hole spacing differs from the specified lead spacing.
- Do not exceed the specified time or temperature limits during soldering.
- Avoid external energy inputs, such as fire or electricity.
- Avoid overload of the capacitors.

The table below summarizes the safety instructions that must always be observed. A detailed description can be found in the relevant sections of the chapters "General technical information" and "Mounting guidelines".

Topic	Safety information	Reference chapter "General technical information"
Storage conditions	Make sure that capacitors are stored within the specified range of time, temperature and humidity conditions.	4.5 "Storage conditions"
Flammability	Avoid external energy, such as fire or electricity (passive flammability), avoid overload of the capacitors (active flammability) and consider the flammability of materials.	5.3 "Flammability"
Resistance to vibration	Do not exceed the tested ability to withstand vibration. The capacitors are tested to IEC 60068-2-6. EPCOS offers film capacitors specially designed for operation under more severe vibration regimes such as those found in automotive applications. Consult our catalog "Film Capacitors for Automotive Electronics".	5.2 "Resistance to vibration"


Topic	Safety information	Reference chapter "Mounting guidelines"
Soldering	Do not exceed the specified time or temperature limits during soldering.	1 "Soldering"
Cleaning	Use only suitable solvents for cleaning capacitors.	2 "Cleaning"
Embedding of capacitors in finished assemblies	When embedding finished circuit assemblies in plastic resins, chemical and thermal influences must be taken into account. Caution: Consult us first, if you also wish to embed other uncoated component types!	3 "Embedding of capacitors in finished assemblies"


B32656S
Snubber (wound)

Symbols and terms

Symbol	English	German
α	Heat transfer coefficient	Wärmeübergangszahl
α_C	Temperature coefficient of capacitance	Temperaturkoeffizient der Kapazität
A	Capacitor surface area	Kondensatoroberfläche
β_C	Humidity coefficient of capacitance	Feuchtekoeffizient der Kapazität
C	Capacitance	Kapazität
C_R	Rated capacitance	Nennkapazität
ΔC	Absolute capacitance change	Absolute Kapazitätsänderung
$\Delta C/C$	Relative capacitance change (relative deviation of actual value)	Relative Kapazitätsänderung (relative Abweichung vom Ist-Wert)
$\Delta C/C_R$	Capacitance tolerance (relative deviation from rated capacitance)	Kapazitätstoleranz (relative Abweichung vom Nennwert)
dt	Time differential	Differentielle Zeit
Δt	Time interval	Zeitintervall
ΔT	Absolute temperature change (self-heating)	Absolute Temperaturänderung (Selbsterwärmung)
$\Delta \tan \delta$	Absolute change of dissipation factor	Absolute Änderung des Verlustfaktors
ΔV	Absolute voltage change	Absolute Spannungsänderung
dV/dt	Time differential of voltage function (rate of voltage rise)	Differentielle Spannungsänderung (Spannungsflankensteilheit)
$\Delta V/\Delta t$	Voltage change per time interval	Spannungsänderung pro Zeitintervall
E	Activation energy for diffusion	Aktivierungsenergie zur Diffusion
ESL	Self-inductance	Eigeninduktivität
ESR	Equivalent series resistance	Ersatz-Serienwiderstand
f	Frequency	Frequenz
f_1	Frequency limit for reducing permissible AC voltage due to thermal limits	Grenzfrequenz für thermisch bedingte Reduzierung der zulässigen Wechselspannung
f_2	Frequency limit for reducing permissible AC voltage due to current limit	Grenzfrequenz für strombedingte Reduzierung der zulässigen Wechselspannung
f_r	Resonant frequency	Resonanzfrequenz
F_D	Thermal acceleration factor for diffusion	Therm. Beschleunigungsfaktor zur Diffusion
F_T	Derating factor	Deratingfaktor
i	Current (peak)	Stromspitze
I_C	Category current (max. continuous current)	Kategoriestrom (max. Dauerstrom)

Symbol	English	German
I_{RMS}	(Sinusoidal) alternating current, root-mean-square value	(Sinusförmiger) Wechselstrom
i_z	Capacitance drift	Inkonstanz der Kapazität
k_0	Pulse characteristic	Impulskennwert
L_S	Series inductance	Serieninduktivität
λ	Failure rate	Ausfallrate
λ_0	Constant failure rate during useful service life	Konstante Ausfallrate in der Nutzungsphase
λ_{test}	Failure rate, determined by tests	Experimentell ermittelte Ausfallrate
P_{diss}	Dissipated power	Abgegebene Verlustleistung
P_{gen}	Generated power	Erzeugte Verlustleistung
Q	Heat energy	Wärmeenergie
ρ	Density of water vapor in air	Dichte von Wasserdampf in Luft
R	Universal molar constant for gases	Allg. Molarkonstante für Gas
R	Ohmic resistance of discharge circuit	Ohmscher Widerstand des Entladekreises
R_i	Internal resistance	Innenwiderstand
R_{ins}	Insulation resistance	Isolationswiderstand
R_P	Parallel resistance	Parallelwiderstand
R_S	Series resistance	Serienwiderstand
S	severity (humidity test)	Schärfegrad (Feuchtestest)
t	Time	Zeit
T	Temperature	Temperatur
τ	Time constant	Zeitkonstante
$\tan \delta$	Dissipation factor	Verlustfaktor
$\tan \delta_D$	Dielectric component of dissipation factor	Dielektrischer Anteil des Verlustfaktors
$\tan \delta_P$	Parallel component of dissipation factor	Parallelanteil des Verlustfaktors
$\tan \delta_S$	Series component of dissipation factor	Serienanteil des Verlustfaktors
T_A	Ambient temperature	Umgebungstemperatur
T_{max}	Upper category temperature	Obere Kategorietemperatur
T_{min}	Lower category temperature	Untere Kategorietemperatur
t_{OL}	Operating life at operating temperature and voltage	Betriebszeit bei Betriebstemperatur und -spannung
T_{op}	Operating temperature	Betriebstemperatur
T_R	Rated temperature	Nenntemperatur
T_{ref}	Reference temperature	Referenztemperatur
t_{SL}	Reference service life	Referenz-Lebensdauer
V_{AC}	AC voltage	Wechselspannung


B32656S
Snubber (wound)

Symbol	English	German
V_C	Category voltage	Kategoriespannung
$V_{C,RMS}$	Category AC voltage	(Sinusförmige) Kategorie-Wechselspannung
V_{CD}	Corona-discharge onset voltage	Teilentlade-Einsatzspannung
V_{ch}	Charging voltage	Ladespannung
V_{DC}	DC voltage	Gleichspannung
V_{FB}	Fly-back capacitor voltage	Spannung (Flyback)
V_i	Input voltage	Eingangsspannung
V_o	Output voltage	Ausgangssspannung
V_{op}	Operating voltage	Betriebsspannung
V_p	Peak pulse voltage	Impuls-Spitzenspannung
V_{pp}	Peak-to-peak voltage Impedance	Spannungshub
V_R	Rated voltage	Nennspannung
$\hat{V}_R$	Amplitude of rated AC voltage	Amplitude der Nenn-Wechselspannung
V_{RMS}	(Sinusoidal) alternating voltage, root-mean-square value	(Sinusförmige) Wechselspannung
V_{SC}	S-correction voltage	Spannung bei Anwendung "S-correction"
V_{sn}	Snubber capacitor voltage	Spannung bei Anwendung "Beschaltung"
Z	Impedance	Scheinwiderstand
e	Lead spacing	Rastermaß

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, MiniBlue, MiniCell, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.