

1. Scope

The present specifications shall apply to an EG01C.

2. Outline

Type	Silicon Diode
Structure	Resin Molded
Applications	High Frequency Rectification

3. Flammability

UL94V-0(Equivalent)


4. Absolute maximum ratings

No.	Item	Symbol	Unit	Rating	Conditions
1	Transient Peak Reverse Voltage	V_{RSM}	V	1000	
2	Peak Reverse Voltage	V_{RM}	V	1000	
3	Average Forward Current	$I_{F(AV)}$	A	0.5	Refer to Derating of 7
4	Peak Surge Forward Current	I_{FSM}	A	10	Half sinewave, one shot
5	I^2t Limiting Value	I^2t	A^2s	0.5	$1\text{msec} \leq t \leq 10\text{msec}$
6	Junction Temperature	T_j	$^{\circ}\text{C}$	-40~+150	
7	Storage Temperature	T_{stg}	$^{\circ}\text{C}$	-40~+150	


5. Electrical characteristics

No.	Item	Symbol	Unit	Value	Conditions
1	Forward Voltage Drop	V_F	V	3.3 max.	$I_F=0.5\text{A}$
2	Reverse Leakage Current	I_R	μA	50 max.	$V_R=V_{RM}$
3	Reverse Leakage Current Under High Temperature	$H \cdot I_R$	μA	500 max.	$V_R=V_{RM}$, $T_j=100^{\circ}\text{C}$
4	Reverse Recovery Time	trr-1	ns	100 max.	$I_F=I_{RP}=100\text{mA}$ 90% Recovery point, $T_j=25^{\circ}\text{C}$
		trr-2	ns	50 max.	$I_F=100\text{mA}$, $I_{RP}=200\text{mA}$ 75% Recovery point, $T_j=25^{\circ}\text{C}$
5	Thermal Resistance	$R_{th(j-l)}$	$^{\circ}\text{C} / \text{W}$	20 max.	Between Junction and Lead

6. Characteristics




7. Derating



8. Package information

8-1Package type, physical dimensions and material



- ☐ 1 The allowance position of Body against the center of whole lead wire is 0.5mm(max.)
- ☐ 2 The centric allowance of lead wire against center of physical body is 0.2mm(max.)
- ☐ 3 The burr may exit up to 2mm from the body of lead


Dimensions in mm

8-2Appearance

The body shall be clean and shall not bear any stain, rust or flaw.

8-3Marking

カソード表示
Cathode Band



Type number EG01C is abbreviated as G^0_C

Lot number 1

First digit: Last digit of Year

Second digit: Month

From 1 to 9 for Jan. to Sep.

O for Oct., N for Nov., and D for Dec.

Lot number 2 (ten days)

- : Top of the month
- : Middle of month
- : End of month