

**Mallory Sonalert Products, Inc.**

Part #:

**SCE028LD3MG3B****Sales Outline Drawing**

Revision:

**C****Specifications:**

|                        |                                                                                            |                            |                             |                            |
|------------------------|--------------------------------------------------------------------------------------------|----------------------------|-----------------------------|----------------------------|
| Sound Level Category:  | Loud                                                                                       | Loud                       | Loud                        | Medium                     |
| Mode of Operation:     | Continuous                                                                                 | Double Pulse               | Quick Pulse                 | Dual Tone                  |
| Loudness @ 2 FT:       | 85 to 95 dB(A) Typ.                                                                        | 85 to 95 dB(A) Typ.        | 85 to 95 dB(A) Typ.         | 75 to 85 dB(A) Typ.        |
| Pulse Rate (PPS):      | N/A                                                                                        | 2                          | 60                          | 7                          |
| Frequency:             | 2900 ± 500 Hz                                                                              | 2900 ± 500 Hz              | 2900 ± 500 Hz               | 3.0 - 2.9 kHz              |
| Connection:            | T-BLOCK ONLY                                                                               | T-BLOCK; BLACK WIRE TO (-) | T-BLOCK; YELLOW WIRE TO (-) | T-BLOCK; BOTH WIRES TO (-) |
| Voltage Rating:        | 16 to 28 VDC                                                                               |                            |                             |                            |
| Current Draw:          | 40mA MAX                                                                                   |                            |                             |                            |
| Housing Material:      | 6/6 Nylon, Color: Black                                                                    |                            |                             |                            |
| Storage Temperature:   | -40° to +85° C                                                                             |                            |                             |                            |
| Operating Temperature: | -40° to +85° C                                                                             |                            |                             |                            |
| Panel Mounting:        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |                            |                             |                            |
| Knurled Nut:           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |                            |                             |                            |
| Weight (Typical):      | 1.6 oz (45g)                                                                               |                            |                             |                            |
| NEMA 3R,4X, & 12:      | Approved with use of ACC03.                                                                |                            |                             |                            |
| cUL Recognition:       | cUL Recognized                                                                             |                            |                             |                            |
| Options:               | Please contact factory.                                                                    |                            |                             |                            |

**Dimensions:** Inches (mm)**cUL Recognized****ROHS Compliant**