POSEICO
POSEICO SPA
POwer SEmiconductors Italian COrporation

POSEICO SPA
Via Pillea 42-44, 16153 Genova - ITALY
Tel. + 39 010 8599400 - Fax + 39 010 8682006
Sales Office:
Tel. + 39 010 8599400 - Fax + 39 010 8681180

FAST SWITCHING THYRISTOR

ATF514

Repetitive voltage up to	**1200 V**
Mean on-state current	**1100 A**
Surge current	**16 kA**
Turn-off time	**20 µs**

FINAL SPECIFICATION

mag 06 - ISSUE : 07


Symbol	Characteristic	Conditions	Tj [°C]	Value	Unit
BLOCKING					
V_{RRM}	Repetitive peak reverse voltage		125	1200	V
V_{RSM}	Non-repetitive peak reverse voltage		125	1300	V
V_{DRM}	Repetitive peak off-state voltage		125	1200	V
I_{RRM}	Repetitive peak reverse current	V=VRRM	125	100	mA
I_{DRM}	Repetitive peak off-state current	V=VDRM	125	100	mA
CONDUCTING					
$I_{T(AV)}$	Mean on-state current	180° sin, 50 Hz, Th=55°C, double side cooled		1100	A
$I_{T(AV)}$	Mean on-state current	180° sin, 1 kHz, Th=55°C, double side cooled		1025	A
I_{TSM}	Surge on-state current, non repetitive	sine wave, 10 ms	125	16	kA
I^2t	I^2t	without reverse voltage		1280 x1E3	A^2s
V_T	On-state voltage	On-state current = 2000 A	25	2,5	V
$V_{T(TO)}$	Threshold voltage		125	1,50	V
r_T	On-state slope resistance		125	0,350	mohm
SWITCHING					
di/dt	Critical rate of rise of on-state current, min	From 75% VDRM up to 1200 A, gate 10V 5 ohm	125	500	A/µs
dv/dt	Critical rate of rise of off-state voltage, min	Linear ramp up to 75% of VDRM	125	600	V/µs
td	Gate controlled delay time, typical	VD=200V, gate source 20V, 10 ohm , tr=.5 µs	25	0,85	µs
tq	Circuit commutated turn-off time	di/dt = 60 A/µs, I = 1000 A dV/dt = 200 V/µs , up to 80% VDRM	125	20	µs
Q rr	Reverse recovery charge	di/dt = 60 A/µs, I = 1000 A	125	130	µC
I rr	Peak reverse recovery current	VR = 50 V		105	A
I_H	Holding current, typical	VD=5V, gate open circuit	25		mA
I_L	Latching current, typical	VD=12V, tp=30µs	25		mA
GATE					
V_{GT}	Gate trigger voltage	VD=5V	25	3,5	V
I_{GT}	Gate trigger current	VD=5V	25	350	mA
V_{GD}	Non-trigger gate voltage, min.	VD=VDRM	125	0,25	V
V_{FGM}	Peak gate voltage (forward)		25	30	V
I_{FGM}	Peak gate current		25	10	A
V_{RGM}	Peak gate voltage (reverse)		25	5	V
P_{GM}	Peak gate power dissipation	Pulse width 100 µs	25	150	W
$P_{G(AV)}$	Average gate power dissipation		25	3	W
MOUNTING					
$R_{th(j-h)}$	Thermal impedance, DC	Junction to heatsink, double side cooled		26	°C/kW
T_j	Operating junction temperature			-30 / 125	°C
F	Mounting force			14.0 / 17.0	kN
	Mass			500	g

ORDERING INFORMATION : ATF514 S 12 A — tq code; standard specification; VDRM&VRRM/100


tq code					
D 10 µs	C 12 µs	B 15 µs	A 20 µs	L 25 µs	
M 30 µs	N 35 µs	P 40 µs	R 45 µs	S 50 µs	
T 60 µs	U 70 µs	W 80 µs	X 100µs	Y 150µs	

SWITCHING CHARACTERISTICS

REVERSE RECOVERY CHARGE
Tj = 125 °C




REVERSE RECOVERY CURRENT
Tj = 125 °C



ta = Irr / (di/dt) tb = trr - ta

Softness (s factor) s = tb / ta

Energy dissipation during recovery Er = Vr · (Qrr - Irr ·ta / 2)




ATF514 FAST SWITCHING THYRISTOR


POSEICO SPA
POwer SEmiconductors Italian COrporation

FINAL SPECIFICATION mag 06 - ISSUE : 07


ON-STATE CHARACTERISTIC
Tj = 125 °C




SURGE CHARACTERISTIC
Tj = 125 °C



TRANSIENT THERMAL IMPEDANCE
DOUBLE SIDE COOLED





Dimensions
in mm

Cathode terminal type DIN 46244 - A 4.8 - 0.8
Gate terminal type AMP 60598 - 1

All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink, surfaces with flatness < .03 mm and roughness < 2 µm.
In the interest of product improvement POSEICO SpA reserves the right to change any data given in this data sheet at any time without previous notice.
If not stated otherwise the maximum value of ratings (simbols over shaded background) and characteristics is reported.

Distributed by