



Part Number ADS-117/883, Sampling A/D Converters

12 bit, 2MHz (2MSPS), Sampling Analog to Digital (A/D) Converter with Three-state output buffers. $\pm 5V$ or 0 to +10V Input range, no pipeline delay, $-55^{\circ}C$ to $+125^{\circ}C$ temperature range, High Reliability 883 Screening.

Image is for illustration purposes only

Specifications

Resolution	12 Bit
Number of Channels	1
Sampling Rate	2 MHz
Acquisition Time	155 ns
Power Consumption	1.6 W
Differential Non-Linearity Error/Other	1.0 LSB
Integral Non-Linearity Error/Other	1 LSB
Package Type	DDIP
Input Range 1st (min)	0 V
Input Range 1st (max)	10 V
Input Range 2nd (min)	-5 V
Input Range 2nd (max)	5 V
Required Supply Voltage 1st	5 V
Required Supply Voltage 3rd	15 V
Required Supply Voltage 4th	-15 V
Total Harmonic Distortion	-78 dB
Signal to Noise Ratio	72 dB
Analog Bandwidth	10 MHz
Operating Temp. Range (min)	$-55^{\circ}C$
Operating Temp. Range (max)	$+125^{\circ}C$
RoHS	No
Status	Recommended for new design

© DATEL is a registered trademark of DATEL, Inc.