



基板取付穴推奨寸法
RECOMMENDED P.C.BOARD HOLE DIM.

注記
NOTE

△ 全極数が偶数の場合にのみ適用。
TO BE APPLIED ONLY WHEN ALL CKTS. ARE EVEN.

34.88	31.68	09-75-2094	5274-09A	9
26.96	23.76	↑ -2074	↑ -07A	7
23	19.8	↑ -2064	↑ -06A	6
19.04	15.84	↑ -2054	↑ -05A	5
15.08	11.88	↑ -2044	↑ -04A	4
11.12	7.92	↓ -2034	↓ -03A	3
7.16	3.96	09-75-2024	5274-02A	2
B	A	オーダー番号 (EDP NO.) ORDER NO. (EDP NO.)	ENG. NO.	極数 CKTS

REVISED EC NO: J2009-2884 DRWN: YSHIBATA 2009/06/24 CHKD: THARUYAMA 2010/03/15 APPR: NUKITA 2010/03/15	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1		DESIGN UNITS METRIC		THIRD ANGLE PROJECTION	
		10 UNDER	±0.2	DRAWN BY	DATE	TITLE KK 3.96 WAFER ASS'Y RIGHT ANGLE WITH LOCK					
		10 OVER 30 UNDER	±0.25	CHECKED BY	DATE	MOLEX INCORPORATED					
		30 OVER	±0.3	APPROVED BY	DATE						
ANGULAR	±3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		DOCUMENT NO.		SHEET NO.			
D	REV	SIZE A3		SEE TABLE SD-5274-001 1 OF 1							