Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Power cable, 3-position, PVC, gray RAL 7001, free cable end, on Socket straight, black, Cable length: 3 m

Product Description

The cable serves to connect 600 class PLD enclosure lights to the supply voltage.

RoHS

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	320.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of cable	3 m
Stripping length of the free conductor end	32 mm (Protective conductor (PE) 39 mm)

Ambient conditions

Degree of protection	IP20
	IP40 (plugged in)

General

Rated current at 40°C	16 A
Rated voltage	250 V AC
Number of positions	3
Coding	black
Insertion/withdrawal cycles	100

Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

Technical data

Material

Material, knurls	not available

Classifications

eCl@ss

eCl@ss 5.1	27049090
eCl@ss 8.0	27379201
eCl@ss 9.0	27141137

ETIM

ETIM 5.0	EC002498

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

UL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 118976

cUL Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 118976

cULus Recognized http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

Accessories

Accessories

Power cable - PLD E 608-CA-3,0/FS/UL - 2702306

Accessories

Installation connector

Connector - PLD E 608-CO-MS - 2702308



Connector for series connection, black, 3-pos.

Power distributor

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.

Phoenix Contact 2016 © - all rights reserved
http://www.phoenixcontact.com