

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
	F3	Obsolescence of P/N 4-825440-0		23JULY2013	SMT	RP	

NUMMER 825440	
VERWENDET FÜR E 92-9802	
WAR NR. —	

POLZ. PRO REIHE	L±0.5	BESTELL-NR.
—	—	—
2	5.08	825 440 -2
3	7.62	-3
4	10.16	-4
5	12.70	-5
6	15.24	-6
7	17.78	-7
8	20.32	-8
9	22.86	-9
10	25.40	1-
11	27.94	1-
12	30.48	1-
13	33.02	1-
14	35.56	1-
15	38.10	1-
16	40.64	1-
17	43.18	1-
18	45.72	1-
19	48.26	1-
20	50.80	2-
21	53.34	2-
22	55.88	2-
23	58.42	2-
24	60.96	2-
25	63.50	2-
26	66.04	2-
27	68.58	2-
28	71.12	2-
29	73.66	2-
30	76.20	3-
31	78.74	3-
32	81.28	3-
33	83.82	3-
34	86.36	3-
35	88.90	3-
36	91.44	3-
37	93.98	3-
38	96.52	3-
39	99.06	3-
40	101.60	4-
41	104.14	4-
42	106.68	4-
43	109.22	4-
44	111.76	4-
45	114.30	4-
46	116.84	4-
47	119.38	4-
48	121.92	4-
49	124.46	4-
50	127.00	5- 825 440 -0

CAD-ORIGINAL
 ZEICHNUNG NICHT ÄNDERN

1

STECKSEITE: IM BEREICH "F" 0.8 μm GOLD ÜBER 1.27 μm NICKEL

LÖTSEITE: MIN. 2.5 μm ZINN ÜBER 1.27 μm NICKEL

KONTAKTSTIFT	Cu Sn	⚠
STIFTGEHÄUSE	PBT GV	
BENENNUNG	WERKSTOFF	OBERFLÄCHE
		FARBE

ZEICHNUNG GÜLTIG AB
KW 39./96

DIMENSIONS: mm		DWN 22.06.84 M.SCHAARSCHMIDT	MATERIAL —	FINISH —		
TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.2 mm 0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± — 4 PLC ± — ANGLES ± —		CHK —	TE Connectivity			
		APVD —				
		PRODUCT SPEC —				
		APPLICATION SPEC —				
WEIGHT —		NAME AMPMODU II STIFTLEISTE ZWEIREIHIG	SIZE A4	CAGE CODE 00779	DRAWING NO C-825440	RESTRICTED TO —

CUSTOMER DRAWING

SCALE 4:1

SHEET 1 OF 2

REV F3


RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

THIS DRAWING IS UNPUBLISHED.

By —
COPYRIGHT —

LOC		DIST		REVISIONS																																																																																																														
—		—		P	LTR	DESCRIPTION	DATE	DWN	APVD																																																																																																									
					—	SEE SHEET 1	—	—	—																																																																																																									
VERWENDET FÜR E 92-9802				CAD-ORIGINAL ZEICHNUNG NICHT ÄNDERN																																																																																																														
WAR NR. —																																																																																																																		
<table><tr><td>Polz. pro Reihe</td><td>L±0.5</td><td colspan="2">Bestell-Nr.</td><td>Bemerkung</td></tr><tr><td>1</td><td>2.54</td><td>5-</td><td>-1</td><td></td></tr><tr><td>2</td><td>5.08</td><td>5-</td><td>-2</td><td></td></tr><tr><td>3</td><td>7.62</td><td>5-</td><td>-3</td><td></td></tr><tr><td>4</td><td>10.16</td><td>5-</td><td>-4</td><td></td></tr><tr><td>5</td><td>12.70</td><td>5-</td><td>-5</td><td></td></tr><tr><td>6</td><td>15.24</td><td>5-</td><td>-6</td><td></td></tr><tr><td>7</td><td>17.78</td><td>5-</td><td>-7</td><td></td></tr><tr><td>8</td><td>20.32</td><td>5-</td><td>-8</td><td></td></tr><tr><td>9</td><td>22.86</td><td>5-</td><td>-9</td><td></td></tr><tr><td>10</td><td>25.40</td><td>6-</td><td>0</td><td></td></tr><tr><td>11</td><td>27.94</td><td>6-</td><td>-1</td><td></td></tr><tr><td>12</td><td>30.48</td><td>6-</td><td>-2</td><td></td></tr><tr><td>13</td><td>33.02</td><td>6-</td><td>-3</td><td></td></tr><tr><td>14</td><td>35.56</td><td>6-</td><td>-4</td><td></td></tr><tr><td>15</td><td>38.10</td><td>6-</td><td>-5</td><td></td></tr><tr><td>16</td><td>40.64</td><td>6-</td><td>-6</td><td></td></tr><tr><td>17</td><td>43.18</td><td>6- 825 440</td><td>-7</td><td>△</td></tr><tr><td>18</td><td>45.72</td><td>6-</td><td>-8</td><td></td></tr><tr><td>19</td><td>48.26</td><td>6-</td><td>-9</td><td></td></tr><tr><td>20</td><td>50.80</td><td>7-</td><td>0</td><td></td></tr></table>										Polz. pro Reihe	L±0.5	Bestell-Nr.		Bemerkung	1	2.54	5-	-1		2	5.08	5-	-2		3	7.62	5-	-3		4	10.16	5-	-4		5	12.70	5-	-5		6	15.24	5-	-6		7	17.78	5-	-7		8	20.32	5-	-8		9	22.86	5-	-9		10	25.40	6-	0		11	27.94	6-	-1		12	30.48	6-	-2		13	33.02	6-	-3		14	35.56	6-	-4		15	38.10	6-	-5		16	40.64	6-	-6		17	43.18	6- 825 440	-7	△	18	45.72	6-	-8		19	48.26	6-	-9		20	50.80	7-	0	
Polz. pro Reihe	L±0.5	Bestell-Nr.		Bemerkung																																																																																																														
1	2.54	5-	-1																																																																																																															
2	5.08	5-	-2																																																																																																															
3	7.62	5-	-3																																																																																																															
4	10.16	5-	-4																																																																																																															
5	12.70	5-	-5																																																																																																															
6	15.24	5-	-6																																																																																																															
7	17.78	5-	-7																																																																																																															
8	20.32	5-	-8																																																																																																															
9	22.86	5-	-9																																																																																																															
10	25.40	6-	0																																																																																																															
11	27.94	6-	-1																																																																																																															
12	30.48	6-	-2																																																																																																															
13	33.02	6-	-3																																																																																																															
14	35.56	6-	-4																																																																																																															
15	38.10	6-	-5																																																																																																															
16	40.64	6-	-6																																																																																																															
17	43.18	6- 825 440	-7	△																																																																																																														
18	45.72	6-	-8																																																																																																															
19	48.26	6-	-9																																																																																																															
20	50.80	7-	0																																																																																																															
△ VERPACKUNG:25 STÜCK IN PLASTIK-DOSE PN 165 439-1 MIT PLASTIK-DECKEL PN 165 440-1																																																																																																																		
△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI																																																																																																																		
△ OBSOLETE																																																																																																																		
<table><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">BENENNUNG</td><td colspan="2">WERKSTOFF</td><td colspan="2">OBERFLÄCHE</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">FARBE</td></tr></table>																						BENENNUNG		WERKSTOFF		OBERFLÄCHE						FARBE																																																																																		
BENENNUNG		WERKSTOFF		OBERFLÄCHE																																																																																																														
				FARBE																																																																																																														
ZEICHNUNG GÜLTIG AB KW 39/96																																																																																																																		
DIMENSIONS: mm		DWN A.HO 07.06.84		MATERIAL —		FINISH —																																																																																																												
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± — 4 PLC ± — ANGLES ± —		CHK M.SCHAARSCHMIDT 13.06.84		 TE Connectivity																																																																																																														
		APVD —																																																																																																																
		PRODUCT SPEC —		NAME AMPMODU II STIFTLEISTE ZWEIREIHIG																																																																																																														
		APPLICATION SPEC —																																																																																																																
		WEIGHT —		SIZE A4		CAGE CODE 00779		DRAWING NO C-825440																																																																																																										
								RESTRICTED TO —																																																																																																										
		CUSTOMER DRAWING		SCALE 4:1		SHEET 2 OF 2		REV F3																																																																																																										



RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

THIS DRAWING IS UNPUBLISHED.

By -
COPYRIGHT -