
Leiditech

PLED06CF

LED Shunt Protection

Description

The open LED protectorprovides a switching electronic shunt path whenan LED in an LED arrayfailsas an opencircuit.This ensures that theentire array of LED s will continue to functioneven if a single LED inthearray does not. This provides higher reliable lighting functions In applications such as headlights, aircrafts, aircraft runway lighting, Roadside warning lights, etc.This device is compatible with one,two and Three watt LEDs that haveanominal 3V forward characteristic.
The PLED® is available in two surface mount packages, the SOD-123 and the Quad Flat Pak No-lead(QFN).The QFN's low profile,chip scalepackage (CSP) is ideal for dense board applications.



Electrcal Characteristics (Tamb=25℃)

Part Number	V_{DRM} breakdown	I_{DRM}	V_{BR} breakdown	I_S	V_T	I_T	`I_H	Critical rate ofrisedV/dt
	Min.	Max.	Max.	Max.	Max.	Max.	Min.	Max.
	V	uA	V	mA	V	A	mA	V
PLED06CF	5.5	10	15	600	1.5	1	5	250V/μs

General Notes:

●All measurements are made at an ambient temperature of 25℃.Ipp applies to -40℃ through +85℃ temperature range.

●Special voltage(VBO and VDRM) and holding current(IH) requirements are available up on request.

Electrical Parameters(Tamb=25℃)


Symbol	Parameter	Symbol	Parameter
V_{DRM}	Stand-off voltage,is measured at I_{DRM}	I_H	Holding current
I_{DRM}	Leakage current,is measured at V_{DRM}	I_T	ON-state current
V_{BR}	Breakover voltage,is measured at 100V/μs	V_T	On-state voltage
I_S	Breadover current		

Download from alldatasheet.com


Thermal Considerations

Package SOD-123	Symbol	Parameter	Value	Unit
	T_J	Operating Junction Temperature	-40 to +150	℃
	T_S	Storage Temperature Range	-60 to +150	℃
	$R_{\theta JA}$	Junction to Ambient on printed circuit	90	℃/W


V-I Characteristics




V_{BR} vs. JunctionTemperature



Normalized DC Holding Current vs. Case Temperature




LED InterferenceTest Circuit



Download from alldatasheet.com

Product Dimensions

Dimension	Inches		Millimeters	
	MIN	MAX	MIN	MAX
A	0.037	0.053	0.94	1.35
A_1	0.00	0.004	0.00	0.10
b	0.020	0.028	0.51	0.71
c	-	0.006	-	0.15
E	0.100	0.112	2.54	2.84
D	0.055	0.071	1.40	1.80
H_E	0.140	0.152	3.56	3.86
L	0.010	-	0.25	-



Summary of Packing Options

Package Type	Description	Packing Quantity	Industry Standard
SOD-123 	Embossed Carrier Reel Pack	3000PCS	EIA-481-D

Shanghai Leiditech Electronic Co.,Ltd
Email: sale1@leiditech.com
Tel : +86- 021 50828806
Fax : +86- 021 50477059

Download from alldatasheet.com