


Rotary Switches

RB1 Series












SWITCHING COMBINATION




11 1 pole 1*2




12 1 pole 1*12




13 1 pole without stop




21 2 poles 2*2




22 2 poles 2*6




23 2 poles without stop




31 3 poles 3*2




32 3 poles 3*4




33 3 poles without stop




41 4 poles 4*2




42 4 poles 4*3



43 4 poles without stop




61 6 poles 6*2




63 6 poles without stop


ACTUATOR OPTIONS



E Extended Actuator




R Recessed Actuator




L Extended with Allu Shaft


P. C. MOUNTING




1 pole




2 poles



3 poles



4 poles



6 poles

How to order:

RB1 [1] [2] [3]

1	ACTUATOR:
E	Extended
R	Recessed
L	Extended with Alluminum Shaft

2	SWITCHING COMBINATION:				
11	12	13	21	22	
23	31	32	33	41	
42	43	61	63		

3	CONTACTS:
S	Shorting (Make before break)
N	Non Shorting (Break before make)

General Specifications:

Voltage Rating: 150 VDC
Current Rating: 130mA
Insulation Resistance: 100MΩ Min.
Indexing Angle: 30°
Operating Life no load: 20,000 cycles Min.
Operating Life at Maxpower: 15,000 cycles Min.
Solder Specification: 250°C 5 seconds
Operating Force: 1 kgf_cm (Max.)