

## Han Guiding PE module, female




Image is for illustration purposes only. Please refer to product description.

Part number	09 14 003 3152
Specification	Han Guiding PE module, female
HARTING eCatalogue	<a href="https://b2b.harting.com/09140033152">https://b2b.harting.com/09140033152</a>

### Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® Guiding module
Description of the module	PE module

### Version

Termination method	Crimp termination
Gender	Female
Number of contacts	2
PE contact	1
Details	Please order crimp contacts separately. Not for Han-Modular® hinged frames!

### Technical characteristics

Conductor cross-section	[0,14] ... [4 mm²]
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	[-40] ... [+125 °C]
Mating cycles	≥500



Pushing Performance

## Technical characteristics

Lock-in range	±4 mm
---------------	-------

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
CE	0

## Commercial data

Packaging size	2
Net weight	9.2 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	90909090 Interim classification (unspecified)