



Product: 29502F

VFD 300% Gnd, 3C+IG #12 Str TC, XLPO Ins+PVC Gnd, OS+TC Brd, Blk TPE Jkt, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable

[Request Sample](#)

Product Description

Belden 300% Ground Extra Flexible VFD, 3 Conductor 12AWG (7x24x34) Tinned Copper, XLPO Insulation M4 Color Code+PVC Insulated Ground, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, Black TPE Outer Jacket, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable 1000V WTTC 600V CIC TC SUN RES OIL RES I&II DIR BUR

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | AC Motor drives, VFD, Variable Frequency drives |
|------------------------|---|

Physical Characteristics (Overall)

Conductor

| Element | AWG | Stranding | Material | No. of Conductors |
|-------------|-----|-----------|--------------------|-------------------|
| | 12 | 7x24x34 | TC - Tinned Copper | 3 |
| Ground Wire | 12 | 7x24x34 | TC - Tinned Copper | |

| | |
|------------------|---|
| Conductor Count: | 3 |
|------------------|---|

Insulation

| Material | Nominal Wall Thickness |
|-------------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.045 in |
| XLP - Cross Linked Polyolefin | 0.045 in |

Color Chart

| Number | Color |
|--------|----------------------|
| 1 | Black and Numbered 1 |
| 2 | Black and Numbered 2 |
| 3 | Black and Numbered 3 |
| 4 | Green/Yellow |

Outer Shield Material

| Type | Layer | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG |
|-------|-------|--------------------|---------------------|--------------|--------------------|---------------|
| Tape | 1 | Aluminum/Polyester | Duofoil® | 100 % | TC - Tinned Copper | 12 |
| Braid | 2 | TC - Tinned Copper | | 85 % | | |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness |
|-------------------------------|------------------|------------------------|
| TPE - Thermoplastic Elastomer | 0.661 in | 0.073 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR |
|-----------------------|
| 1.6 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
|---|---|

| | |
|----------|----------|
| 26 pF/ft | 47 pF/ft |
|----------|----------|

Inductance

| |
|---------------------------|
| Nominal Inductance |
| 0.197 µH/ft |

Impedance

| |
|---|
| Nominal Characteristic Impedance |
| 71 Ohm |

Current

| |
|--|
| Max. Recommended Current [A] |
| 30 Amps per conductor @ 30°C (per NEC) |

Voltage

| |
|--|
| UL Voltage Rating |
| 1000 V RMS (Flexible Motor Supply Cable) |

Temperature Range

| | |
|-----------------------|----------------------|
| UL Temp Rating: | 90°C Dry, 90°C Wet |
| Operating Temp Range: | -40C To +90C Wet/Dry |
| Wet Temp Range: | -40°C To +90 °C |

Mechanical Characteristics

| | |
|---------------------------------------|----------------|
| Bulk Cable Weight: | 250 lbs/1000ft |
| Max Recommended Pulling Tension: | 336 lbs |
| Min Bend Radius (Continuous Flexing): | 5 in |
| Min Bend Radius/Minor Axis: | 3.3 in |

Standards

| | |
|--------------------------|--------------------------------|
| NEC Articles: | 336 - ER |
| NEC/(UL) Specification: | TC-ER, WTTC, XHHW-2 |
| CEC/C(UL) Specification: | 600V Type CIC TC |
| Other Specification: | 1000V UL Flexible Motor Supply |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-13 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |

Suitability

| | |
|------------------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |
| Suitability - Sunlight Resistance: | Yes |

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|---|
| UL Flammability: | UL1685 UL Loading |
| CSA Flammability: | FT4 |
| IEEE Flammability: | 1202, 383 Vertical Tray Flame Test (70,000 BTU) |
| UL voltage rating: | 1000 V RMS (Flexible Motor Supply Cable) |

Part Number

Variants

| | | |
|--------|-------|-----|
| Item # | Color | UPC |
|--------|-------|-----|

| | | |
|----------------|-------|--------------|
| 29502F 0101000 | Black | 612825367208 |
| 29502F 0105000 | Black | 612825367215 |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.223 Revision Date: 09-10-2019 |
|----------------------|--|

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.