

LED DOT MATRIX

BL-M20X571

Features:

- Ø 53.10mm (2.0") 1/5 dot matrix LED display.
- Ø Low current operation.
- Ø Excellent character appearance.
- Ø Easy mounting on P.C. Boards or sockets.
- Ø I.C. Compatible.
- Ø ROHS Compliance.



Super Bright

Electrical-optical characteristics: (Ta=25 °C) (Test Condition: IF=20mA)

Part No			Chip			VF Unit:V		Iv TYP.(mcd)
Row Cathode Column Anode	Row Anode Column Cathode	Emitted Color	Material	λp (nm)		Typ	Max	
BL-M20A571S-XX	BL-M20B571S-XX	Hi Red	GaAlAs/GaAs,SH	660		1.85	2.20	120
BL-M20A571D-XX	BL-M20B571D-XX	Super Red	GaAlAs/GaAs,DH	660		1.85	2.20	140
BL-M20A571UR-XX	BL-M20B571UR-XX	Ultra Red	GaAlAs/GaAs,DDH	660		1.85	2.20	160
BL-M20A571E-XX	BL-M20B571E-XX	Orange	GaAsP/GaP	635		2.10	2.50	90
BL-M20A571Y-XX	BL-M20B571Y-XX	Yellow	GaAsP/GaP	585		2.10	2.50	90
BL-M20A571G-XX	BL-M20B571G-XX	Green	GaP/GaP	570		2.20	2.50	95

Ultra Bright

Electrical-optical characteristics: (Ta=25 °C) (Test Condition: IF=20mA)

Part No		Chip			VF Unit:V		Iv TYP.(mcd)
Row Cathode Column Anode	Row Anode Column Cathode	Emitted Color	Material	λp (nm)	Typ	Max	
BL-M20A571UHR-XX	BL-M20B571UHR-XX	Ultra Red	AlGaInP	645	2.10	2.50	160
BL-M20A571UE-XX	BL-M20B571UE-XX	Ultra Orange	AlGaInP	630	2.10	2.50	130
BL-M20A571YO-XX	BL-M20B571YO-XX	Ultra Amber	AlGaInP	619	2.10	2.50	130
BL-M20A571UY-XX	BL-M20B571UY-XX	Ultra Yellow	AlGaInP	590	2.10	2.50	130
BL-M20A571UG-XX	BL-M20B571UG-XX	Ultra Green	AlGaInP	574	2.20	2.50	170
BL-M20A571PG-XX	BL-M20B571PG-XX	Ultra Pure Green	InGaN	525	3.80	4.50	200
BL-M20A571B-XX	BL-M20B571B-XX	Ultra Blue	InGaN	470	2.70	4.20	90
BL-M20A571W-XX	BL-M20B571W-XX	Ultra White	InGaN	/	2.70	4.20	130

--XX: Surface / Lens color :

Number	0	1	2	3	4	5
Ref Surface Color	White	Black	Gray	Red	Green	
Epoxy Color	Water clear	White diffused	Red Diffused	Green Diffused	Yellow Diffused	

LED DOT MATRIX

BL-M20X571

Absolute maximum ratings (Ta=25°C)

Parameter		S	D	UR	E	Y	G	Unit
Forward Current I_F		25	25	25	25	25	30	mA
Power Dissipation P_d		60	60	60	60	60	65	mW
Reverse Voltage V_R		5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)		150	150	150	150	150	150	mA
Operation Temperature T_{OPR}	-40 to +80							°C
Storage Temperature T_{STG}	-40 to +85							°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)							°C

Absolute maximum ratings (Ta=25°C)


Parameter	UHR	UE	YO	UY	UG	PG	B	W	Unit
Forward Current I_F	30	30	30	30	30	30	30	30	mA
Power Dissipation P_d	75	65	65	65	75	110	120	120	mW
Reverse Voltage V_R	5	5	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	150	100	100	mA
Operation Temperature T_{OPR}	-40 to +80								°C
Storage Temperature T_{STG}	-40 to +85								°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)								°C

LED DOT MATRIX


BL-M20X571

Package configuration & Internal circuit diagram


BL-M20X571 Series



BL-M20A571



BL-M20B571




Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is ± 0.25 (0.01") unless otherwise noted.
3. Specifications are subject to change without notice.


LED DOT MATRIX

BL-M20X571


Typical electrical-optical characteristics curves:




- | | |
|---|--------------------------------------|
| (1) - GaAsP/GaAs 655nm/Red | (9) - GaAlAs 880nm |
| (2) - GaP 570nm/Yellow Green | (10) - GaAs/GaAs & GaAlAs/GaAs 940nm |
| (3) - GaAsP/GaP 585nm/Yellow | (A) - GaN/SiC 430nm/Blue |
| (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red | (B) - InGaN/SiC 470nm/Blue |
| (5) - GaP 700nm/Bright Red | (C) - InGaN/SiC 505nm/Ultra Green |
| (6) - GaAlAs/GaAs 660nm/Super Red | (D) - InGaAl/SiC 525nm/Ultra Green |
| (8) - GaAsP/GaP 610nm/Super Red | |




FORWARD VOLTAGE (Vf)
FORWARD CURRENT VS.
FORWARD VOLTAGE





FORWARD CURRENT (mA)
RELATIVE LUMINOUS
INTENSITY VS. FORWARD
CURRENT



AMBIENT TEMPERATURE Ta(°C)
FORWARD CURRENT VS. AMBIENT
TEMPERATURE



AMBIENT TEMPERATURE Ta(°C)



NOTE: 25°C free air temperature unless otherwise specified

LED DOT MATRIX

BL-M20X571

Packing and weighting

