




FEATURES

- Frequency Range: 1410 - 1440 MHz
- Tuning Voltage: 1-5 Vdc
- MINI-14S - Style Package

APPLICATIONS

- Wireless radios
- Mobile Communications
- Basestations



PERFORMANCE SPECIFICATIONS

	VALUE	UNITS
Oscillation Frequency Range	1410 - 1440	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-112	dBc/Hz
Harmonic Suppression (2nd, typ.)	-28	dBc
Tuning Voltage	1-5	Vdc
Tuning Sensitivity (avg.)	15	MHz/V
Power Output	-1.5±3	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	50	pF
Pushing	<2	MHz/V
Pulling (14 dB Return Loss, Any Phase)	<2	MHz
Operating Temperature Range	-40 to 85	°C
Package Style	MINI-14S	

POWER SUPPLY REQUIREMENTS

Supply Voltage (Vcc, nom.)	5	Vdc
Supply Current (Icc, typ.)	27	mA

All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES

- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

