January 9, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

HIGH DENSITY, HIGH VOLTAGE, STANDARD RECOVERY RECTIFIER ASSEMBLY

- 2.5A forward current
- Low reverse leakage current
- Corona free design
- Easy aluminum base mount
- Low forward voltage drop


QUICK REFERENCE DATA

- V_R = 5kV & 10kV
- I_F = 2.5A
- t_{rr} = 2.0µS
- I_R = 1.0µA

ABSOLUTE MAXIMUM RATINGS

	Symbol	SDH5KS	SDH10KS	Unit
Working reverse voltage	V_{RWM}	5.0	10.0	kV
Surge reverse voltage	V_{RSM}	5.5	11.0	kV
Average forward current in air @ 25°C in oil @ 55°C	$I_{F(AV)}$	← 2.5 → ← 2.5 →		A A
Non-repetitive surge current t_p = 8.3mS, @ 25°C	I_{FSM}	← 150 →		A
Storage temperature range	T_{STG}	← -55 to +150 →		°C
Operating temperature range	T_{OP}	← -55 to +150 →		°C
Body length ±0.030"	dim C	3.36	4.04	inches

MECHANICAL



G22A

DIM*	DIMENSIONS MM MIN	MM MAX	INCHES MIN	INCHES MAX	NOTE
A	15.2	16.8	.60	.66	-
B	-	33.5	-	1.32	-
C	SEE TABLE				-
D	3.6	5.1	.14	.20	-
E	8.6	10.2	.34	.40	-
F	5.6	7.1	.22	.28	-
G	19.6	21.1	.77	.83	-
H	11.9	13.5	.47	.53	-
J	8.9	10.4	.35	.41	-
K	2.3	3.8	.09	.15	-
L	5.6	7.1	.22	.28	-
X	1.0	-	.04	-	DIA

© 1997 SEMTECH CORP.

January 9, 1998

ELECTRICAL CHARACTERISTICS

	Symbol	SDH5KS	SDH10KS	Unit
Max. forward voltage drop @ I_F = 3.0A, T_j = 25°C	V_F	6.0	12.0	V
Max. reverse leakage current @ V_{RWM}, T_j = 25°C	I_R	← 1.0 →		µA
@ V_{RWM}, T_j = 100°C	I_R	← 20 →		µA
Max. reverse recovery time [1] 0.5A I_F to 1.0A I_R. Recovers to 0.25A I_{RR}.	t_{rr}	← 2.0 →		µS
Max. fusing current t_p = 8.3mS	I^2t	← 94 →		A^2S

[1] Measured on discrete devices prior to assembly




Fig 1. Forward voltage drop as a function of forward current for use with multiplication table 1.

Multiplication tables for fig 1.

SDH5KS	X-axis x1
SDH10KS	X-axis x2

© 1997 SEMTECH CORP.