Product data sheet

Specifications



Harmony XB4, Block for test "light function" with integral LED, double, 48…230 V AC

ZBZM156

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 40.00 USD

Main

Range of product	Harmony XB5 Harmony XB4
Product or Component Type	Block for test light
Product Compatibility	Integral LED
Light block type	Double block for test light function
[Us] rated supply voltage	48...230 V AC
Electrical Connection	Wires

Complementary

Material	Plastic
Electrical shock protection class	Class I Harmony XB4 IEC 60536 Class II Harmony XB5 IEC 60536
Product Weight	0.02 lb(US) (0.01 kg)

Environment

Ambient Air Temperature for Storage	-40…158 °F (-40…70 °C)
Ambient Air Temperature for Operation	-13…158 °F (-25…70 °C)
Standards	EN 60947-1 EN 60947-5-4 IEC 60947-5-4 IEC 60947-5-1 CSA C22.2 No 14 UL 508 EN 60947-5-5 IEC 60947-5-5 EN 60947-5-1 JIS C 4520 IEC 60947-1
Product Certifications	DNV GL LROS (Lloyds register of shipping) UL Listed BV CSA
Vibration resistance	5 gn 2…500 Hz)IEC 60068-2-6
Shock resistance	30 gn 18 ms IEC 60068-2-27 50 gn 11 ms IEC 60068-2-27

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW
Discount Schedule	CS2
GTIN	3389118030114
Nbr. of units in pkg.	1
Package weight(Lbs)	1.02 oz (29 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.09 in (5.3 cm)
Package 1 width	1.34 in (3.4 cm)
Package 1 Length	3.46 in (8.8 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Weight	3.93 lb(US) (1.784 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months

Wiring Diagram

