

HIRSCHMANN MOBILITY



GPS Adhesive Antenna

GPS 10 P/series
Pt no.
602-431-...

- For interior and exterior mounting at vehicles
- Low current consumption

Subject to alterations


Technical data

Dimensions	34 mm x 38 mm x 12,8 mm	
Weight	70 g	
Operation Temperature range	-40° C - + 85° C	
Storage Temperature range	-40° C - + 85° C	
Protection class	IP6k7 (acc. ISO 20653)	
Frequency range	1,57542 GHz \pm 1,023 MHz (L1-band)	
Impedance	50 Ohm	
Gain	min.	2 dBic*
Amplification	typ.	26 dB \pm 2 dB
Noise figure	typ.	1,4 dB
Voltage supply	2,7 V - 5,5 VDC	
Current consumption	\leq 13 mA @ 5 V \pm 0.5 V (typ. 10 mA)	
Cable type	RG 174	
Cable length	3000 mm	
Connector	...-001:	SMA male
	...-002:	FAKRA female, Code C, blue


GPS ADHESIVE ANTENNA

GPS 10 P/series Pt no. 602-431-...

Technical drawings



Installation



www.te.com/hirschmann-mobility

hirschmann-mobility@te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS are trademarks. Hirschmann is a trademark.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2019 TE Connectivity Ltd. family of companies All Rights Reserved.