

Part Number: C4311A

Revision Level: 3

Date: 7/13/2007

2C 20 SOLID TC SR-PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#20 AWG Solid Tinned Copper	0.032" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.052" nom.
Cable:	2 conductors @ 2.00" LHL.	0.104" nom.
Jacket:	0.032" Wall Polyvinyl Chloride	0.168" +/- 0.008"
Print Legend:	CAROL (R) 20 AWG -- C4311A -- 75C E111240-8 CM (UL) C (UL) OR AWM STYLE 2464 --- CSA LL69381 CMG -- MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000' TO 0')	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V _{rms}
CONDUCTOR D.C. RESISTANCE:	10.5 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	28 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red