




➔ Specifications

Parameter	Specification	
Center Wavelength	1310 nm & 1550 nm	
Bandwidth	± 40 nm	
Attenuation Range	1-30 dB	
Attenuation Tolerance	± 10%	
Return Loss	50 dB	
Fiber Type	SMF 28e	
Operating Temperature	- 40° C ~ + 85° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Light Duty (B)	3.0 mm () x 55 mm (L)
	Medium Duty (L)	3.0 mm () x 60 mm (L)
	Heavy Duty (K, R)	100.0 mm x 12.0 mm x 8.0 mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

➔ Ordering Information

F A -  -  -  - 			
Attenuation XX: xx dB 03: 3 dB 10: 10 dB	Pigtail Length 1: 1 meter 2: 2 meter S: Special	Pigtail Style (=Package style) B: bare fiber L: 900 μm loose tube K: 2mm cable R: 3mm cable	Connector 0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC