

VS150E-3/A



Sales Region	Worldwide
Series	VS-E
Status	Production
Feature	
Option	With cover type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 132V
Input Voltage Range[DC]	110 to 175V
Efficiency	80% Typ.
Rated Output Voltage[DC]	3.3V
Output Voltage Range[DC]	2.97 to 3.63V
Maximum Output Current	30A
Maximum Output Power	99W

Cases Shape & Size

Case'□ shape	PC board
Width(W)	85mm Nom.
Height(H)	47mm Nom.
Depth(D)	188mm Nom.
Weight	600g Typ.

Other

Operating Temp. Range	-10 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an Appendix 12
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.