

P-tec Corporation Tel:(866)695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa CO 81101 Fax:(719) 589 3592
 www.p-tec.net sales@p-tec.net



PL07 Series 3mm (T1) LED

Features

- *Popular 3mm Lens Style with small Flange
- *1 GaN/SiC Blue Chip used
- *Color Diffused Lens with a Wide Viewing Angle
- *High Intensity
- *Low Current Requirement
- *Reliable and Rugged
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	135mW
Reverse Voltage (<50μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL07-CDB01	Blue	GaN/SiC	428	466	80°	3.8	4.5	4.5	10.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1 mm down the leads.

