


Nut Torque: 5 ~ 14Nm  
 Operating Pressure: 400gf ± 150gf  
 Operating Stroke: 1.5mm ± 0.3  
 Protection Grade: IP65  
 Function: (ON)-OFF  
 Base: PA66  
 Shell: Brass, Ni Plating  
 Button: SUS  
 Rating: 0.2A 250V AC/0.5A 12V DC  
 Contact Resistance: 50mΩ MAX.  
 Insulation Resistance: 100MΩ MIN.  
 Dielectric Strength: 1500V/AC of 1 minute  
 Electrical life: 50,000 cycles  
 Mechanical life: 200,000 cycles  
 Operating Temperature: -20°C~80°C  
 Relative Air Humidity: 45%~85%  
 Safety Approval:



公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
				版本 VERSION	比例尺 SCALE	日期 DATE		
				A0	1:1	2021.02.22		
						孙成	PBM-12M11-HT-N-NN-B8S	PBM-12M11-HT-N-NN-B8S_A0