

LDC-150 Series

Compact, LED, 150W Constant Current AC/DC Power Supply



Key Features:

- 150W Output Power
- UL 8750 Approved
- Constant Current Output
- Active PFC
- 90 - 305 VAC Input
- IP65 / IP67 Rated
- Meets EN 55015, EN 61547
- Dimming Function
- >50 kHour Life Expectancy
- Lightning Surge Protection
- Over Volt/Temp Protection

Electrical Specifications

Specifications typical @ +25°C, 230 VAC input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.



Input						
Parameter	Conditions	Min.	Typ.	Max.	Units	
Input Voltage Range		90		305	VAC	
Input Frequency		47		63	Hz	
Inrush Current, See Note 1	230 VAC		75		A Pk	
Input Current	115 VAC		2.10		A	
	230 VAC		0.90			
	264 VAC		0.80			
			0.98 @ 115 VAC			
Power Factor Correction			0.95 @ 230 VAC			
			0.93 @ 264 VAC			
Total Harmonic Distortion (THD)	See Note 2			10	%	
Turn On Delay, See Note 3	115 VAC		1.5		S	
	230 VAC		0.5			
Leakage Current	277 VAC			0.75	mA	

Output						
Parameter	Conditions	Min.	Typ.	Max.	Units	
Output Current Accuracy			±5.0		%	
Line Regulation	V _{IN} = Min to Max		±1.0		%	
Ripple & Noise (20 MHz)	See Note 4		2.0		V P-P	
Output Ripple Current			±5.0		%	
Hold-Up Time	115 VAC	12.0			mS	
Over Temperature Protection	±10%, Autorecovery		85		°C	
Short Circuit Protection	Continuous (Autorecovery)					
Overload Protection	Autorecovery	95		107	%I _{OUT}	

General							
Parameter	Conditions	Min.	Typ.	Max.	Units		
Isolation Voltage, 60S	Input to Output	3,750			VAC		
	Input to FG	2,000					
	Output to FG	500					
Insulation Resistance	Input to Output	100 MΩ / 500 VDC / 25°C / 70% RH					
	Input to FG						
	Output to FG						

EMI Characteristics						
Parameter	Standard					
EMI	EN 55015; EN 6100-3-2, -3; FCC Part 18; CNS 14115; GB 17743					
EMS	EN 61547; EN 61000-4-2, -3, -4, -5, -6, -8, -11; GB 17625.1					
Surge	10 kV (L/N - FG), 5 kV (L-N)/1.2 x 50 μS					

Environmental						
Parameter	Conditions	Min.	Typ.	Max.	Units	
Operating Temperature Range	Ambient	-40	+25	+70	°C	
Storage Temperature Range		-40		+85	°C	
Cooling	Free Air Convection (See Derating Curve on Page 2)					
Humidity	RH, Non-condensing			95	%	

Physical						
Parameter	See Mechanical Diagrams (Page 4)					
Case Size						
Weight	33.1 Oz (950g)					

Reliability Specifications						
Parameter	Conditions	Min.	Typ.	Max.	Units	
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	220			kHours	
Life Expectancy	See Note 5	50			kHours	
Safety Standards	UL 8750 Approved, Meets EN 61347, GB 19510.1, GB 19510.14					
Vibration	5 - 500 Hz, 1G, 1 Oct/Min, 2 Cycles, Period for 75 Min. Each Along X, Y, & Z Axis					



MicroPower Direct

292 Page Street
Suite D
Stoughton, MA 02072
USA

T: (781) 344-8226
F: (781) 344-8481
E: sales@micropowerelectronics.com
W: www.micropowerelectronics.com



www.micropowerelectronics.com

Model Number	Output			Output Power (W)	Efficiency (% Typ)	
	Current		Voltage Range (VDC)			
	Max (mA)	Adj. Range (mA)				
LDC-150-2450 x	2,450	1,650 - 2,450	32 - 58	62 - 80	142	91
LDC-150-3150 x	3,150	2,000 - 3,150	32 - 49	54 - 73	154	91
LDC-150-3500 x	3,500	2,200 - 3,500	27 - 42	49 - 65	147	91
LDC-150-4550 x	4,550	2,750 - 4,550	25 - 35	41 - 55	159	91


Notes:

1. Inrush current is given for a cold start at 25°C.
2. Total Harmonic Distortion (THD) is specified with an input of 230 VAC/50 Hz at full load.
3. Turn on delay is specified at full load.
4. Ripple & noise is measured at 20 MHz. Connection to the unit is made with a 0.1 µF ceramic capacitor and a 22 µF electrolytic capacitor connected in parallel.
5. Life expectancy is calculated at 230 VAC, full load and a case temp of +70°C.
6. Recovery from an over voltage fault is automatic.


Package Type

Model	Ingress Protection	Dimming Function
LDC-150-xxxx A	IP65	Adjust by internal, variable resistor
LDC-150-xxxx B	IP67	Adjust by external resistor, DC voltage level or PWM signal


Derating Curve: Temperature




Derating Curve: Input Voltage




Efficiency vs Load: LDC-150-4550




PFC vs Load: LDC-150-4550



Functional Block Diagram



Dimming Mode: B Model



With the LDC-150 "B" model, the output current level can be adjusted (Dimmed) by three different methods; Resistive, Analog or Digital. Adjustments are made using the +DIM and -DIM inputs.

Resistive: Connect a 0.1 to 10 kΩ resistor between the DIM+ (Blue) and DIM- (White) wires

Input Frequency	10 kΩ	20 kΩ	30 kΩ	40 kΩ	50 kΩ	60 kΩ	70 kΩ	80 kΩ	90 kΩ	100 kΩ	Open
Percentage of Rated Current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95~105%

Analog: Apply 1 VDC to 10 VDC level between the DIM+ (Blue) and DIM- (White) wires

Adjust Voltage	1 VDC	2 VDC	3 VDC	4 VDC	5 VDC	6 VDC	7 VDC	8 VDC	9 VDC	10 VDC	Open
Percentage of Rated Current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95~105%


Digital: Apply a PWM signal (100 Hz - 3 kHz) between the DIM+ (Blue) and DIM- (White) wires

Duty Cycle	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Open
Percentage of Rated Current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95~105%

Notes:

1. The -DIM (White) and -LED (Black) wires should not be connected.
2. The Dimming function will not turn the lighting fixture totally off. For more info on how to do this, please contact the factory

Mechanical Dimensions: A Model




Wire Connections: Input

Color	Function
Green/Yellow	Field Ground
Brown	AC-Line
Blue	AC-Neutral

Wire Connections: Output

Color	Function
Black	-LED
Red	+LED

Mechanical Dimensions: B Model (Dimming Function)



Wire Connections: Input

Color	Function
Green/Yellow	Field Ground
Brown	AC-Line
Blue	AC-Neutral

Wire Connections: Output

Color	Function
White	-DIM
Blue	+DIM
Black	-LED
Red	+LED



MicroPower Direct
We Power Your Success - For Less!