General Cable Product Data Sheet

Part Number: C3245	Revision Level: 1	Date: 10/26/2007

4C 14 SOLID BC HALAR PVC **Fire Alarm/Life Safety Cable**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#14 AWG Solid Bare Copper	0.064” nom.
Insulation:	0.0185” Wall Halar	0.101” nom.
Cable:	4C @ 4.00” LHL	0.246” nom.
Jacket:	0.020” Wall FLEXGUARD* - Red	0.286" +/- 0.014"
Print Legend:	***E86522-F CAROL CABLE TYPE FPLP 14 AWG -- (UL) -- MID-CAP --(seq. Footage mkgs every 2 ft. in ascending order) i.e. 000003, 000006, etc.***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 760
UL Standard 1424	Type FPLP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	300V
CONDUCTOR D.C. RESISTANCE:	2.5 Ohms/1000 ft nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	Red
3	Brown
4	Blue

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

**FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.*