

## Housing - HC-STA-B16-HHWD-1STP29-EL-AL - 1412706

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing B16, With double locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, lateral, Height: 76 mm, Cable gland: none, Gland: no, 1x Pg29, Standard

### Why buy this product

- good shielding in the event of electromagnetic interference



### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 STK    |
| Custom tariff number | 85389099 |
| Country of origin    | China    |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Height | 76 mm   |
| Width  | 44 mm   |
| Length | 93.5 mm |

#### Ambient conditions

|                                        |                                                           |
|----------------------------------------|-----------------------------------------------------------|
| Degree of protection of housing (IP)   | IP66                                                      |
|                                        | IP69K (ISO 20653:2013-02, with suitable screw connection) |
|                                        | IP67                                                      |
| Degree of protection of housing (NEMA) | 4                                                         |
|                                        | 4X                                                        |
|                                        | 12                                                        |
| Ambient temperature (operation)        | -40 °C ... 125 °C                                         |

## Housing - HC-STA-B16-HHWD-1STP29-EL-AL - 1412706


### Technical data

#### General

|                              |                                                             |
|------------------------------|-------------------------------------------------------------|
| Note                         | For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K |
| Size                         | B16                                                         |
| Housing type                 | Sleeve housing                                              |
| Locking type                 | With double locking latch                                   |
| No. of cable outlets         | 1                                                           |
| Cable exit                   | lateral                                                     |
| Screw connection             | none                                                        |
| Type of the screw connection | 1x Pg29                                                     |
| Housing material             | Die-cast aluminum, salt water resistant                     |
| Housing surface material     | Uncoated                                                    |
| Material lock                | PA                                                          |

### Drawings

Dimensional drawing



Dimensional drawing

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000437 |
|----------|----------|

### Approvals

#### Approvals

## Housing - HC-STA-B16-HHWD-1STP29-EL-AL - 1412706

### Approvals

---

Approvals

EAC / GL

---

Ex Approvals

---

Approvals submitted

---

### Approval details

|     |
|-----|
| EAC |
|-----|

|    |
|----|
| GL |
|----|

### Accessories

#### Accessories

##### Full screw connection

Cable gland - G-INS-PG29-M68N-NNES-S - 1411176



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 18 mm ... 25 mm, Shielding: No, Connecting thread: Pg29, Color: silver

---

Cable gland - G-INSEC-PG29-M68N-NNES-S - 1411201



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 18 mm ... 25 mm, Shielding: yes, Connecting thread: Pg29, Color: silver

---

### Housing latches

## Housing - HC-STA-B16-HHWD-1STP29-EL-AL - 1412706

### Accessories

Housing brackets - HC-STA-B10-24-DL-PLBK - 1412886



Double locking latch for B10 / B16 / B24 housing, HC-EVO....AL and HC-STA....AL

---

### Labeled device marker

Plastic label - US-EMLP (20X9) CUS - 0830085



Plastic label, can be ordered: By card, white, labeled according to customer specifications, Mounting type: Adhesive, Lettering field: 20 x 9 mm

---

### Protective cover

Protective covers - HC-B16-BCSFD-P-BK - 1414629



HEAVYCON protective cover, B16, for HC-EVO-B16... supporting base element, for double locking latch, with retaining cord with combination eyelet, IP54