XC221A Series

1.2V Input / Output Rail To Rail CMOS Op Amp

■GENERAL DESCRIPTION

The XC221A series is an input / output rail to rail CMOS Op Amp.

With rail to rail functions, operation is guaranteed from power supplies as low as 1.2V. Moreover, since the XC221A series comes in an ultra small SOT-25 package, the series is particularly suited for use with various types of portable phones. Bandwidths of 550kHz and slew rates of 0.5V can be achieved even with power consumption as low as 100μA.

Even with large capacitance levels of CL = 200pF (unity gain connection), the XC221A series will not be susceptible to oscillation.


■APPLICATIONS

- ●Palmtop computers, PDAs
- ●Cellular and portable phones
- ●Portable audio systems
- ●Various battery powered systems

■FEATURES

Operating Voltage Range: 1.2 ~ 10V (single cell)
: ±0.6 ~ 5V (+ve/-ve supply)
Output Signal **:** 0.1~2.9V (3V single cell, RL=2kΩ)
Gain Bandwidth **:** 550kHz (15μA: 210kHz)
Slew Rate **:** 0.5V/μs
High Capacitance Load **:** CL=200pF
Low Supply Current **:** 100μA, 15μA
Input / Output Rail To Rail Operation
Package **:** SOT-25
Environmentally Friendly: EU RoHS Compliant, Pb Free

■PIN CONFIGURATION



SOT-25
(TOP VIEW)

■PIN ASSIGNMENT

PIN NUMBER	SYMBOL	FUNCTION
1	V_{OUT}	Output Pin
2	V_{DD}	Positive Power Supply Pin
3	IN_{+}	Positive Input
4	IN_{-}	Negative Input
5	V_{SS}	Negative Power Supply Pin

■PRODUCT CLASSIFICATION

●Ordering Information

XC221A①②③④⑤⑥−⑦ (*1)

DESIGNATOR	DESCRIPTION	SYMBOL	DESCRIPTION
①	The Number of Channels	1	One channel
②	Supply Current	1	15μA
		2	100μA
③	Internal Standard Number	0	Fixed
④	Load Capacitance	0	200pF
⑤⑥-⑦	Packages Taping Type (*2)	MR	SOT-25
		MR-G	SOT-25 (Halogen & Antimony free)

(*1) The "-G" suffix indicates that the products are Halogen and Antimony free as well as being fully RoHS compliant.

(*2) The device orientation is fixed in its embossed tape pocket. For reverse orientation, please contact your local Torex sales office or representative. (Standard orientation: ⑤R-⑦, Reverse orientation: ⑤L-⑦)

■ABSOLUTE MAXIMUM RATINGS

Ta = 25℃, V_{SS} = 0V

PARAMETER	SYMBOL	RATINGS	UNITS
V_{DD} Pin Voltage	V_{DD}	-0.3 ～ 12.0	V
OUT Pin Voltage	V_{OUT}	-0.3 ～ 12.0	V
IN Pin Voltage	V_{IN+}	-0.3～V_{DD}+0.3	V
IN/ Pin Voltage	V_{IN-}	-0.3～V_{DD}+0.3	V
OUT Pin Current	I_{OUT}	±100	mA
Power Dissipation	Pd	150	mW
Operating Temperature Range	Topr	-30 ～ +80	℃
Storage Temperature Range	Tstg	-40 ～ +125	℃

RAIL-TO-RAIL is a trademark of Motorola.

■ELECTRICAL CHARACTERISTICS

XC221A1100 I_{DD} =15μA Ta = 25℃

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Voltage	V_{DD}		1.2	-	10.0	V
Supply Current	I_{DD}	V_{DD} = 3V	10	15	23	μA
		V_{DD} = 1.2V	2.5	8	23	μA
Input Offset Voltage	V_{OF}		-	-	20.0	mV
Input Offset Current	I_{OF}		-	1	-	pA
Input Bias Current	IB		-	1	-	pA
Input Resistance	R_{IN}		-	1	-	TΩ
Large Signal Voltage Gain	A_{VD}		75	110	-	dB
Common Mode Rejection Ratio	CMRR	0≦V_{CM}≦3.0V	60	75	-	dB
Power Supply Rejection Ratio	PSRR+	V_{DD} = 3 to 10V, V_{SS} = 0V, V_{OUT} = 1.5V	60	75	-	dB
	PSRR-	V_{SS}=-3 to -10V, V_{DD}= 0V, V_{OUT}= -1.5V	60	75	-	dB
Output Voltage Range	V_{OUT}	R_L = ∞	0.05	-	V_{DD}-0.05	V
		V_{DD} = 1.2V, R_L = 47kΩ (to V_{DD}/2)	0.10	-	1.10	V
		V_{DD} = 3V, R_L = 2kΩ(to V_{DD}/2)	0.10	-	2.90	V
		V_{DD} = 5V, R_L = 2kΩ(to V_{DD}/2)	0.10	-	4.90	V
		V_{DD} = 10V, R_L = 2kΩ(to V_{DD}/2)	0.10	-	9.80	V
Gain Bandwidth	F_T	V_{DD} = 3V	-	210	-	kHz
Slew Rate	S_R	V_{DD} = 3V	-	0.07	-	V/μsec

Test Conditions :Unless otherwise stated, V_{DD} = 3.0V, V_{SS} = 0V, V_{CM} = V_{OUT} = V_{DD} / 2, RL = 1MΩ (to V_{SS}), C_L = 10pF (to V_{SS})

XC221A1200 I_{DD} =100μA Ta = 25℃


PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Voltage	V_{DD}		1.2	-	10.0	V
Supply Current	I_{DD}	V_{DD} = 3V	67	100	150	μA
		V_{DD} = 1.2V	16.75	50.00	150.00	μA
Input Offset Voltage	V_{OF}		-	-	20.0	mV
Input Offset Current	I_{OF}		-	1	-	pA
Input Bias Current	IB		-	1	-	pA
Input Resistance	R_{IN}		-	1	-	TΩ
Large Signal Voltage Gain	A_{VD}		75	110	-	dB
Common Mode Rejection Ratio	CMRR	0≦V_{CM}≦3.0V	60	75	-	dB
Power Supply Rejection Ratio	PSRR+	V_{DD}=3 to 10V, V_{SS} = 0V, V_{OUT} = 1.5V	60	75	-	dB
	PSRR-	V_{SS}=-3 to -10V, V_{DD}=0V, V_{OUT}=-1.5V	60	75	-	dB
Output Voltage Range	V_{OUT}	R_L = ∞	0.05	-	V_{DD}-0.05	V
		V_{DD} = 1.2V, R_L = 47kΩ (to V_{DD}/2)	0.10	-	1.10	V
		V_{DD} = 3V, R_L = 2kΩ(to V_{DD}/2)	0.10	-	2.90	V
		V_{DD} = 5V, R_L = 2kΩ(to V_{DD}/2)	0.10	-	4.90	V
		V_{DD} = 10V, R_L = 2kΩ(to V_{DD}/2)	0.10	-	9.80	V
Gain Bandwidth	F_T	V_{DD} = 3V	-	550	-	kHz
Slew Rate	S_R	V_{DD} = 3V	-	0.50	-	V/μsec

Test Conditions :Unless otherwise stated, V_{DD} = 3.0V, V_{SS} = 0V, V_{CM} = V_{OUT} = V_{DD} / 2, R_L = 1MΩ (to V_{SS}), CL = 10pF (to V_{SS})


■TYPICAL PERFORMANCE CHARACTERISTICS

●XC221A1100 <15μA>


(1) Voltage Gain vs. Phase Margin




(2) Sink Current vs. Output Voltage




(3) Source Current vs. Output Voltage



(4) Supply Current vs. Power Supply Voltage




(5) Supply Current vs. Ambient Temperature




■TYPICAL PERFORMANCE CHARACTERISTICS (Continued)


●XC221A1100 <15μA> (Continued)

(6) Power Supply Rejection Ratio vs. Frequency






(7) Large Signal Input / Output Response




(8) Small Signal Input / Output Response




■TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

●XC221A1200 <100μA>


(1) Voltage Gain vs. Phase Margin




(2) Sink Current vs. Output Voltage




(3) Source Current vs. Output Voltage



(4) Supply Current vs. Power Supply Voltage




(5) Supply Current vs. Ambient Temperature




■TYPICAL PERFORMANCE CHARACTERISTICS (Continued)


●XC221A1200 <100μA> (Continued)

(6) Power Supply Rejection Ratio vs. Frequency






(7) Large Signal Input / Output Response




(8) Small Signal Input / Output Response




■PACKAGING INFORMATION

●SOT-25



■MARKING RULE



SOT-25
(TOP VIEW)

① represents product series and supply current

MARK	PRODUCT SERIES	SUPPLY CURRENT
$\overline{1}$	XC221A11	15μA
$\overline{2}$	XC221A12	100μA

② based on internal standards

③ represents load capacitance

MARK	LOAD CAPACITANCE
0	200pF

④ represents the production lot number
0 to 9, A to Z repeated (G, I, J, O, Q, W excluded)

1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this datasheet.
4. The products in this datasheet are not developed, designed, or approved for use with such equipment whose failure of malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.
   (e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this datasheet within the specified ranges.
   Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this datasheet may be copied or reproduced without the prior permission of TOREX SEMICONDUCTOR LTD.

TOREX SEMICONDUCTOR LTD.