
CERMET TRIMMING POTENTIOMETERS

■ SINGLE TURNS/THROUGH-HOLE

				
Model	24	25	62	77(Note B)
Size[Note A]	0.157" (4mm)	1/4" (6.35mm)	1/4" (6.35mm)	3/8" (9.53mm)
Electrical Travel	190°	210°	220°	244°
Resistance Range	10~10MΩ	10~2MΩ	10~2MΩ	10~2MΩ
Tolerance	±20% (±10% Available)	±20% (±10% Available)	±10% (<100Ω= ±20%)	±10% (<100Ω= ±20%)
TCR(ppm/℃)	±100 (<200Ω= ±250)	±100 (<200Ω= ±250)	±100 (<100Ω= ±250)	±100 (<100Ω= ±250)
Contact Resistance Variance Max.	2% (<200Ω=3Ω)	1% (<100Ω=1Ω)	1% (<100Ω=1Ω)	1% (<100Ω=1Ω)
Seal	85℃ Fluorinert	85℃ Fluorinert	85℃ Fluorinert	85℃ Fluorinert
Adjustment style				
Top	24U③ 24W⑤	25P② 25U③ 25W⑤	62P⑤ PF 62M②	72P, PT②, RP 72PI③, 72PM④, 72PX, RPX①
Side, Edge Mount	24S⑥	25S② 25V⑤ 25X②		72RX, X, XT② 72RW, XL, RXL⑤ 72XW, RXW④
Bottom			62B①	
Packing Options				
Bulk	Standard	NA	Standard	Standard
Tubes	N/A	Standard		P, PM, X, XL XW, RW
Tape&Reel	U	U, V	N/A	RWF(Note C)
Ammo Pack	N/A	U, V	N/A	RWF(Note C)

Note A: Dimensions shown are for popular pin styles. Consult data sheet for complete information.
Note B: Optional adjustment knob version available(Models 72PT& / 72XT)
Note C: "F" is added to pin style for tape& reel and ammo pack.

■ PC BOARD PATTERNS/THROUGH HOLE/inch (mm)

