International
IOR Rectifier

PD - 95685A

HFA30PA60CPbF

HEXFRED™


Ultrafast, Soft Recovery Diode

Features


- Ultrafast Recovery
- Ultrasoft Recovery
- Very Low I_{RRM}
- Very Low Q_{rr}
- Specified at Operating Conditions
- Lead-Free

Benefits

- Reduced RFI and EMI
- Reduced Power Loss in Diode and Switching Transistor
- Higher Frequency Operation
- Reduced Snubbing
- Reduced Parts Count



V_R = 600V
V_F(typ.)* = 1.2V
$I_{F(AV)}$ = 15A
Q_{rr} (typ.)= 80nC
I_{RRM} (typ.) = 4.0A
t_{rr}(typ.) = 19ns
$di_{(rec)M}/dt$ (typ.)* = 160A/µs



TO-247AC

Description

International Rectifier's HFA30PA60C is a state of the art center tap ultra fast recovery diode. Employing the latest in epitaxial construction and advanced processing techniques it features a superb combination of characteristics which result in performance which is unsurpassed by any rectifier previously available. With basic ratings of 600 volts and 15 amps per Leg continuous current, the HFA30PA60C is especially well suited for use as the companion diode for IGBTs and MOSFETs. In addition to ultra fast recovery time, the HEXFRED product line features extremely low values of peak recovery current (I_{RRM}) and does not exhibit any tendency to "snap-off" during the t_b portion of recovery. The HEXFRED features combine to offer designers a rectifier with lower noise and significantly lower switching losses in both the diode and the switching transistor. These HEXFRED advantages can help to significantly reduce snubbing, component count and heatsink sizes. The HEXFRED HFA30PA60C is ideally suited for applications in power supplies and power conversion systems (such as inverters), motor drives, and many other similar applications where high speed, high efficiency is needed.

Absolute Maximum Ratings (per Leg)

	Parameter	Max.	Units
V_R	Cathode-to-Anode Voltage	600	V
I_F @ T_C = 100°C	Continuous Forward Current	15	A
I_{FSM}	Single Pulse Forward Current	150	
I_{FRM}	Maximum Repetitive Forward Current	60	
P_D @ T_C = 25°C	Maximum Power Dissipation	74	W
P_D @ T_C = 100°C	Maximum Power Dissipation	29	
T_J	Operating Junction and	-55 to +150	C
T_{STG}	Storage Temperature Range		

* 125°C

Electrical Characteristics (per Leg) @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Test Conditions
V_{BR}	Cathode Anode Breakdown Voltage	600	–––	–––	V	I_R = 100µA
V_{FM}	Max Forward Voltage	–––	1.3	1.7	V	I_F = 15A
		–––	1.5	2.0		I_F = 30A See Fig. 1
		–––	1.2	1.6		I_F = 15A, T_J = 125°C
I_{RM}	Max Reverse Leakage Current	–––	1.0	10	µA	V_R = V_R Rated See Fig. 2
		–––	400	1000		T_J = 125°C, V_R = 0.8 x V_R Rated
C_T	Junction Capacitance	–––	25	50	pF	V_R = 200V See Fig. 3
L_S	Series Inductance	–––	12	–––	nH	Measured lead to lead 5mm from package body

Dynamic Recovery Characteristics (per Leg)@ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Test Conditions	
t_{rr}	Reverse Recovery Time	–––	19	–––	ns	I_F = 1.0A, di_f/dt = 200A/µs, V_R = 30V	
t_{rr1}	See Fig. 5, 10	–––	42	60		T_J = 25°C	I_F = 15A
t_{rr2}		–––	70	120		T_J = 125°C	
I_{RRM1}	Peak Recovery Current	–––	4.0	6.0	A	T_J = 25°C	V_R = 200V
I_{RRM2}	See Fig. 6	–––	6.5	10		T_J = 125°C	
Q_{rr1}	Reverse Recovery Charge	–––	80	180	nC	T_J = 25°C	di_f/dt = 200A/µs
Q_{rr2}	See Fig. 7	–––	220	600		T_J = 125°C	
$di_{(rec)M}/dt1$	Peak Rate of Fall of Recovery Current	–––	250	–––	A/µs	T_J = 25°C	
$di_{(rec)M}/dt2$	During t_b See Fig. 8	–––	160	–––		T_J = 125°C	

Thermal - Mechanical Characteristics (per Leg)

	Parameter	Min.	Typ.	Max.	Units
T_{lead}①	Lead Temperature	–––	–––	300	°C
R_{thJC}	Junction-to-Case, Single Leg Conducting	–––	–––	1.7	K/W
	Junction-to-Case, Both Legs Conducting	–––	–––	0.85	
R_{thJA}②	Thermal Resistance, Junction to Ambient	–––	–––	40	
R_{thCS}③	Thermal Resistance, Case to Heat Sink	–––	0.25	–––	
Wt	Weight	–––	6.0	–––	g
		–––	0.21	–––	(oz)
	Mounting Torque	6.0	–––	12	Kg-cm
		5.0	–––	10	lbf•in

① 0.063 in. from Case (1.6mm) for 10 sec
② Typical Socket Mount
③ Mounting Surface, Flat, Smooth and Greased




Fig. 1 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current, (per Leg)




Fig. 2 - Typical Reverse Current vs. Reverse Voltage, (per Leg)




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage, (per Leg)




Fig. 4 - Maximum Thermal Impedance Z_{thJC} Characteristics, (per Leg)




Fig. 5 - Typical Reverse Recovery Time vs. di_f/dt, (per Leg)




Fig. 6 - Typical Recovery Current vs. di_f/dt, (per Leg)




Fig. 7 - Typical Stored Charge vs. di_f/dt, (per Leg)




Fig. 8 - Typical $di_{(rec)M}/dt$ vs. di_f/dt, (per Leg)





Fig. 9 - Reverse Recovery Parameter Test Circuit



1. di_f/dt - Rate of change of current through zero crossing
2. I_{RRM} - Peak reverse recovery current
3. trr - Reverse recovery time measured from zero crossing point of negative going I_F to point where a line passing through 0.75 I_{RRM} and 0.50 I_{RRM} extrapolated to zero current
4. Q_{rr} - Area under curve defined by t_{rr} and I_{RRM}


$$Q_{rr} = \frac{t_{rr} \times I_{RRM}}{2}$$

5. $di_{(rec)M}/dt$ - Peak rate of change of current during t_b portion of t_{rr}

Fig. 10 - Reverse Recovery Waveform and Definitions

Ordering Information Table


Device Code



1	-	Hexfred Family		
2	-	Process Designator	A	= subs. elec. irrad.
			B	= subs. Platinum
3	-	Current Rating	(30	= 30A)
4	-	Package Outline	(PA	= TO-247, 3 pins)
5	-	Voltage Rating	(60	= 600V)
6	-	Configuration	(C	= Center Tap Common Cathode)


Note: PbF suffix at the end of the part number indicates Lead-Free

TO-247AC Package Outline



Conform to JEDEC outline TO-247AC (TO-3P)
Dimensions in millimeters and (inches)

TO-247AC Part Marking Information



Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.10/04