



Nut Torque: 5 ~ 14Nm  
 Operating Pressure: 350gf ±80gf  
 Operating Stroke: 2.8mm±0.3mm  
 Protection Grade: IP65, IK08  
 Function: ON-OFF  
 Contact: Silver Alloy  
 Base: PPA66  
 Shell: Brass, Ni Plating  
 Button: SUS  
 Rating (Resistive load): 3A 250V AC  
 Contact Resistance: 50mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Dielectric Strength: 1500V AC 1 minute  
 Electrical life: 50,000 cycles  
 Mechanical life: 100,000 cycles  
 Operating Temperature: -20°C~80°C  
 Relative Air Humidity: 45%~85%  
 Safety Approval:



公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
						孙成	PBM-16Z11-FT-N-NN-B85-A3	PBM-16Z11-FT-N-NN-B85-A3-A0