CD74FCT861A

Data sheet acquired from Harris Semiconductor
SCHS268

January 1997

BiCMOS FCT Interface Logic, 10-Bit Bus Transceiver, Three-State

NOT RECOMMENDED FOR NEW DESIGNS
Use CMOS Technology

Features

- **Buffered Inputs**
- **Typical Propagation Delay: 6.0ns at V_{CC} = 5V, T_A = 25°C, C_L = 50pF**
- **CD74FCT861A**
  - **Noninverting**
- **SCR Latchup Resistant BiCMOS Process and Circuit Design**
- **Speed of Bipolar FAST™/AS/S**
- **48mA Output Sink Current**
- **Output Voltage Swing Limited to 3.7V at V_{CC} = 5V**
- **Controlled Output Edge Rates**
- **Input/Output Isolation to V_{CC}**
- **BiCMOS Technology with Low Quiescent Power**


Ordering Information

PART NUMBER	TEMP. RANGE (°C)	PACKAGE	PKG. NO.
CD74FCT861AM	0 to 70	24 Ld SOIC	M24.3

NOTE: When ordering the suffix M package, use the entire part number. Add the suffix 96 to obtain the variant in the tape and reel.

Pinout

CD74FCT861A
(SOIC)
TOP VIEW




CAUTION: These devices are sensitive to electrostatic discharge. Users should follow proper IC Handling Procedures.

FAST™ is a trademark of Fairchild Semiconductor.

Copyright © Harris Corporation 1996

File Number **2392.2**

Functional Diagram



TRUTH TABLE (Note 1)


INPUTS				OUTPUTS		
$\overline{OEBA}$	$\overline{OEAB}$	B	A	B	A	FUNCTION
L	H	L	N/A	N/A	L	B Data to A Bus
L	H	H	N/A	N/A	H	B Data to A Bus
H	L	N/A	L	L	N/A	A Data to B Bus
H	L	N/A	H	H	N/A	A Data to B Bus
H	H	X	X	Z	Z	High Z
L	L	-	-	-	-	A Data to B Bus, B Data to A Bus

NOTE:

1. H= HIGH Voltage Level
   L = LOW Voltage Level
   N/A = Not Applicable
   X = Immaterial
   Z = HIGH Impedance

IEC Logic Symbol

CD74FCT861A



Absolute Maximum Ratings

DC Supply Voltage (V_{CC}) . . . . . -0.5V to 6V
DC Diode Current, I_{IK} (For V_I < -0.5V) . . . . . -20mA
DC Output Diode Current, I_{OK} (for V_O < -0.5V) . . . . . -50mA
DC Output Sink Current per Output Pin, IO 70mA
DC Output Source Current per Output Pin, IO . . . . . -30mA
DC V_{CC} Current (I_{CC}) 264mA
DC Ground Current (I_{GND}) 500mA

Thermal Information

Thermal Resistance (Typical, Note 2) θ_{JA} ($^oC/W$)
SOIC Package 75
Maximum Junction Temperature . . . . . 150^oC
Maximum Storage Temperature Range . . . . . -65^oC to 150^oC
Maximum Lead Temperature (Soldering 10s) . . . . . 300^oC
(Lead Tips Only)

Operating Conditions

Operating Temperature Range, T_A . . . . . 0^oC to 70^oC
Supply Voltage Range, V_{CC} . . . . . 4.75V to 5.25V
DC Input Voltage, V_I . . . . . 0 to V_{CC}
DC Output Voltage, V_O . . . . . 0 to $\leq V_{CC}$
Input Rise and Fall Slew Rate, dt/dv . . . . . 0 to 10ns/V

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

NOTE:

2. θ_{JA} is measured with the component mounted on an evaluation PC board in free air.

Electrical Specifications Commercial Temperature Range 0^oC to 70^oC, V_{CC} Max = 5.25V, V_{CC} Min = 4.75V

PARAMETER	SYMBOL	TEST CONDITIONS		V_{CC} (V)	AMBIENT TEMPERATURE (T_A)				UNITS
					25^oC		0^oC TO 70^oC		
		V_I (V)	I_O (mA)		MIN	MAX	MIN	MAX	
High Level Input Voltage	V_{IH}			4.75 to 5.25	2	-	2	-	V
Low Level Input Voltage	V_{IL}			4.75 to 5.25	-	0.8	-	0.8	V
High Level Output Voltage	V_{OH}	V_{IH} or V_{IL}	-15	Min	2.4	-	2.4	-	V
Low Level Output Voltage	V_{OL}	V_{IH} or V_{IL}	48	Min	-	0.55	-	0.55	V
High Level Input Current	I_{IH}	V_{CC}		Max	-	0.1	-	1	µA
Low Level Input Current	I_{IL}	GND		Max	-	-0.1	-	-1	µA
Three State Leakage Current	I_{OZH}	V_{CC}		Max	-	0.5	-	10	µA
	I_{OZL}	GND		Max	-	-0.5	-	-10	µA
Input Clamp Voltage	V_{IK}	V_{CC} or GND	-18	Min	-	-1.2	-	-1.2	V
Short Circuit Output Current (Note 3)	I_{OS}	V_O = 0 V_{CC} or GND		Max	-75	-	-75	-	mA
Quiescent Supply Current, MSI	I_{CC}	V_{CC} or GND	0	Max	-	8	-	80	µA
Additional Quiescent Supply Current per Input Pin TTL Inputs High, 1 Unit Load	ΔI_{CC}	3.4V (Note 4)		Max	-	1.6	-	1.6	mA

NOTES:

3. Not more than one output should be shorted at one time. Test duration should not exceed 100ms.
4. Inputs that are not measured are at V_{CC} or GND.
5. FCT Input Loading: All inputs are 1 unit load. Unit load is ΔI_{CC} limit specified in Static Characteristics Chart, e.g., 1.6mA Max at 70^oC.


Switching Specifications Over Operating Range FCT Series t_r, t_f = 2.5ns, C_L = 50pF, R_L (Figure 1)

PARAMETER	SYMBOL	V_{CC} (V)	25°C	0°C TO 70°C		UNITS
			TYP	MIN	MAX	
Propagation Delays Data to Outputs	t_{PLH}, t_{PHL}	5 (Note 6)	6	1.5	8	ns
Output Enable to Output	t_{PZL}, t_{PZH}	5	9	1.5	12	ns
Output Disable to Output	t_{PLZ}, t_{PHZ}	5	7.5	1.5	10	ns
Power Dissipation Capacitance	C_{PD} (Note 7)	-	-	-	-	pF
Minimum (Valley) V_{OHV} During Switching of Other Outputs (Output Under Test Not Switching)	V_{OHV}	5	0.5	-	-	V
Maximum (Peak) V_{OLP} During Switching of Other Outputs (Output Under Test Not Switching)	V_{OLP}	5	1	-	-	V
Input Capacitance	C_I	-	-	-	10	pF
Three-State Output Capacitance	C_O	-	-	-	15	pF

NOTES:

6. 5V: Minimum is at 5.25V for 0°C to 70°C, Maximum is at 4.75V for 0°C to 70°C, Typical is at 5V.
7. C_{PD}, measured per flip-flop, is used to determine the dynamic power consumption.
   P_D (per package) = $V_{CC}\ I_{CC} + \Sigma(V_{CC}^2\ f_I\ C_{PD} + V_O^2\ f_O C_L + V_{CC}\ \Delta I_{CC}\ D)$ where:
   V_{CC} = supply voltage
   ΔI_{CC} = flow through current x unit load
   C_L = output load capacitance
   D = duty cycle of input high
   f_O = output frequency
   f_I = input frequency

Test Circuits and Waveforms



NOTE:

8. Pulse Generator for All Pulses: Rate ≤ 1.0MHz; Z_{OUT} ≤ 50Ω; t_f, t_r ≤ 2.5ns.

FIGURE 1. TEST CIRCUIT

SWITCH POSITION

TEST	SWITCH
t_{PLZ}, t_{PZL}, Open Drain	Closed
t_{PHZ}, t_{PZH}, t_{PLH}, t_{PHL}	Open

DEFINITIONS:

C_L = Load capacitance, includes jig and probe capacitance.

R_T = Termination resistance, should be equal to Z_{OUT} of the Pulse Generator.

V_{IN} = 0V to 3V.

Input: $t_r = t_f$ = 2.5ns (10% to 90%), unless otherwise specified




FIGURE 2. SETUP, HOLD, AND RELEASE TIMING




FIGURE 3. PULSE WIDTH




FIGURE 4. ENABLE AND DISABLE TIMING





FIGURE 5. PROPAGATION DELAY

Test Circuits and Waveforms (Continued)



NOTES:

9. V_{OLP} is measured with respect to a ground reference near the output under test. V_{OHV} is measured with respect to V_{OH}.
10. Input pulses have the following characteristics:
    $P_{RR} \leq 1MHz$, $t_r = 2.5ns$, $t_f = 2.5ns$, skew 1ns.
11. R.F. fixture with 700MHz design rules required. IC should be soldered into test board and bypassed with 0.1µF capacitor. Scope and probes require 700MHz bandwidth.

FIGURE 6. SIMULTANEOUS SWITCHING TRANSIENT WAVEFORMS

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)
CD74FCT861AM	OBSOLETE	SOIC	DW	24		TBD	Call TI	Call TI
CD74FCT861AM96	OBSOLETE	SOIC	DW	24		TBD	Call TI	Call TI

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.


(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

DW (R–PDSO–G24) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M–1994.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
D. Falls within JEDEC MS–013 variation AD.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		**Applications**	
Audio	www.ti.com/audio	Communications and Telecom	www.ti.com/communications
Amplifiers	amplifier.ti.com	Computers and Peripherals	www.ti.com/computers
Data Converters	dataconverter.ti.com	Consumer Electronics	www.ti.com/consumer-apps
DLP® Products	www.dlp.com	Energy and Lighting	www.ti.com/energy
DSP	dsp.ti.com	Industrial	www.ti.com/industrial
Clocks and Timers	www.ti.com/clocks	Medical	www.ti.com/medical
Interface	interface.ti.com	Security	www.ti.com/security
Logic	logic.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Power Mgmt	power.ti.com	Transportation and Automotive	www.ti.com/automotive
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com	Wireless	www.ti.com/wireless-apps
RF/IF and ZigBee® Solutions	www.ti.com/lprf		
	TI E2E Community Home Page		e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2011, Texas Instruments Incorporated