

## Han 24HPR EasyCon cover without entry



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 40 024 9908  |
| Specification      | Han 24HPR EasyCon cover without entry   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09400249908">https://b2b.harting.com/09400249908</a> |

### Identification

|                             |   |
|-----------------------------|---|
| Category                    | Hoods/Housings                            |
| Series of hoods/housings    | Han <sup>®</sup> HPR EasyCon              |
| Type of hood/housing        | Mounting cover                            |
| Description of hood/housing | for surface mounted housings<br>for hoods |

### Version

|                      |   |
|----------------------|---|
| Locking type         | Screw locking                                 |
| Size                 | 24 HPR  |
| Field of application | Hoods/housings for harsh outdoor environments |

### Technical characteristics

|  |                                |
|--|--------------------------------|
| Tightening torque                      | 6 Nm Mounting cover            |
|  | 6 Nm Distance bolt             |
|  | 6 Nm Fixing screws             |
| Limiting temperature                   | -40 ... +125 °C                |
| Degree of protection acc. to IEC 60529 | IP65                           |
|  | IP68                           |
|  | IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E     | 4                              |
|  | 4X                             |
|  | 12                             |

### Material properties

|                         |                     |
|-------------------------|---------------------|
| Material (hood/housing) | Aluminium die-cast  |
|                         | Corrosion resistant |



Pushing Performance

## Material properties

|                             |                      |
|-----------------------------|----------------------|
| Surface (hood/housing)      | Powder-coated        |
| Colour (hood/housing)       | RAL 9005 (jet black) |
| Material (seal)             | NBR                  |
| RoHS                        | compliant            |
| ELV status                  | compliant            |
| China RoHS                  | e                    |
| REACH Annex XVII substances | No                   |
| REACH ANNEX XIV substances  | No                   |
| REACH SVHC substances       | No                   |

## Specifications and approvals

|           |  |
|-----------|--|
| Approvals | DNV GL   |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1                                      |
| Net weight                     | 284 g                                  |
| Country of origin              | Germany                                |
| European customs tariff number | 85389099                               |
| eCl@ss                         | 27440208 Cap for industrial connectors |