

Semiconductor *Data Sheet*

NPN Epitaxial Planar Transistor


Description

FMBT1815





Mechanical Dimensions



Maximum Ratings

Ratings	Symbol	Value	Units
Collector - Emitter Voltage	V_{CEO}	50	V
Collector - Base Voltage	V_{CBO}	60	V
Emitter - Base Voltage	V_{EBO}	5.0	V
Collector Current (Continuous)	I_C	150	mA
Total Device Dissipation FR-5 Board (Note1) T_A = 25°C	P_D	125	mW
Junction and Storage Temperature	T_J, T_{STG}	-55 to 150	°C

Electrical Characteristics @ 25°C

Characteristic	Symbol	Min	Max	Unit
Collector - Emitter Breakdown Voltage (I_C = 1.0mA)	$V_{BR(CEO)}$	50	---	V
Collector - Base Breakdown Voltage (I_C = 0.1mA)	$V_{BR(CBO)}$	60	---	V
Emitter - Base Breakdown Voltage (I_E = 0.01mA)	$V_{BR(EBO)}$	5.0	---	V
Collector Cutoff Current (V_{CB} = 60V)	I_{CBO}	---	0.1	µA
Emitter Cutoff Current (V_{EB} = 5.0V)	I_{EBO}	---	0.1	µA
DC Current Gain	H_{FE}			---
(I_C = 2.0 mA, V_{CE} = 6.0 V)*		120	600	
(I_C = 150 mA, V_{CE} = 6.0 V)		25	---	
Collector - Emitter Saturation Voltage (I_C = 100 mA, I_B = 10 mA)	$V_{CE(sat)}$	---	0.25	Vdc
Base - Emitter Saturation Voltage (I_C = 100 mA, I_B = 10 mA)	$V_{BE(sat)}$	---	1.0	Vdc
Current - Gain - Bandwidth Product (I_C = 1.0 mA, V_{CE} = 10 V, f = 100 MHz)	f_T	80	---	MHz
Output Capacitance (V_{CB} = 10 V, f = 1.0 MHz)	C_{ob}	---	3.5	pF

*** Classification of h_{FE}**

Rank	C4Y	C4G	C4B
Range	120-240	200-400	350-600

FMBT1815 NPN
Epitaxial Planar Transistor

