COMPLEMENTARY NPN / PNP SMALL SIGNAL SURFACE MOUNT TRANSISTOR


Features & Benefits

- Complementary Pairs One 2222A Type (NPN)
- One 2907A Type (PNP)
- Ideal for Low Power Amplification and Switching
- **Totally Lead-Free & Fully RoHS compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**


Mechanical Data

- Case: SOT363
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish – Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.006 grams (approximate)


SOT363



Top View



Device Symbol




Top View
Pin-Out

Ordering Information (Note 4)

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
MMDT2227-7-F	K27	7	8	3,000

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at http://www.diodes.com.

Marking Information



K27 = Product Type Marking Code
YM = Date Code Marking
Y = Year (ex: X = 2010)
M = Month (ex: 9 = September)

Date Code Key

Year	2010	2011	2012	2013	2014	2015	2016	2017
Code	X	Y	Z	A	B	C	D	E

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

© Diodes Incorporated

Maximum Ratings, 2222A Type (NPN) (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	75	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter-Base Voltage	V_{EBO}	6	V
Continuous Collector Current	I_C	600	mA

Maximum Ratings, 2907A Type (PNP) (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-60	V
Collector-Emitter Voltage	V_{CEO}	-60	V
Emitter-Base Voltage	V_{EBO}	-6.0	V
Continuous Collector Current	I_C	-600	mA

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Power Dissipation	(Notes 5)	P_D	200	mW
Thermal Resistance, Junction to Ambient	(Notes 5)	$R_{\theta JA}$	625	°C/W
Thermal Resistance, Junction to Case	(Note 6)	$R_{\theta JC}$	150	
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150	°C

Notes: 5. Device mounted on 1 inch x 0.85 inch x 0.062 inch FR-4 PCB
6. Thermal resistance from junction to the top of package

© Diodes Incorporated

Electrical Characteristics, 2222A Type (NPN) (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 7)					
Collector-Base Breakdown Voltage	BV_{CBO}	75	—	V	I_C = 100μA, I_E = 0
Collector-Emitter Breakdown Voltage	BV_{CEO}	40	—	V	I_C = 10mA, I_B = 0
Emitter-Base Breakdown Voltage	BV_{EBO}	6.0	—	V	I_E = 100μA, I_C = 0
Collector Cutoff Current	I_{CBO}	—	10	nA μA	V_{CB} = 60V, I_E = 0 V_{CB} = 60V, I_E = 0, T_A = +150°C
Collector Cutoff Current	I_{CEX}	—	10	nA	V_{CE} = 60V, $V_{EB(off)}$ = 3.0V
Emitter Cutoff Current	I_{EBO}	—	10	nA	V_{EB} = 5.0V, I_C = 0
Base Cutoff Current	I_{BL}	—	20	nA	V_{CE} = 60V, $V_{EB(off)}$ = 3.0V
ON CHARACTERISTICS (Note 7)					
DC Current Gain	h_{FE}	35 50 75 100 40 50 35	— — — 300 — — —	—	I_C = 100μA, V_{CE} = 10V I_C = 1.0mA, V_{CE} = 10V I_C = 10mA, V_{CE} = 10V I_C = 150mA, V_{CE} = 10V I_C = 500mA, V_{CE} = 10V I_C = 10mA, V_{CE} = 10V, T_A = -55°C I_C = 150mA, V_{CE} = 1.0V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	—	0.3 1.0	V	I_C = 150mA, I_B = 15mA I_C = 500mA, I_B = 50mA
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	0.6 —	1.2 2.0	V	I_C = 150mA, I_B = 15mA I_C = 500mA, I_B = 50mA
SMALL SIGNAL CHARACTERISTICS					
Output Capacitance	C_{obo}	—	8	pF	V_{CB} = 10V, f = 1.0MHz, I_E = 0
Input Capacitance	C_{ibo}	—	25	pF	V_{EB} = 0.5V, f = 1.0MHz, I_C = 0
Current Gain-Bandwidth Product	f_T	300	—	MHz	V_{CE} = 20V, I_C = 20mA, f = 100MHz
Noise Figure	NF	—	4.0	dB	V_{CE} = 10V, I_C = 100μA, R_S = 1.0kΩ, f = 1.0kHz
SWITCHING CHARACTERISTICS					
Delay Time	t_d	—	10	ns	V_{CC} = 30V, I_C = 150mA, $V_{BE(off)}$ = - 0.5V, I_{B1} = 15mA
Rise Time	t_r	—	25	ns	
Storage Time	t_s	—	225	ns	V_{CC} = 30V, I_C = 150mA, I_{B1} = I_{B2} = 15mA
Fall Time	t_f	—	60	ns	

Notes: 7. Pulse test: Pulse width ≤ 300μs, duty cycle ≤ 2%.




Fig. 1 (2222A) Typical Capacitance




Fig. 2 Typical Collector Saturation Region (2222A Type - NPN)

© Diodes Incorporated

Electrical Characteristics, 2907A Type (PNP) (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 8)					
Collector-Base Breakdown Voltage	BV_{CBO}	-60	—	V	I_C = -100μA, I_E = 0
Collector-Emitter Breakdown Voltage	BV_{CEO}	-60	—	V	I_C = -10mA, I_B = 0
Emitter-Base Breakdown Voltage	BV_{EBO}	-6.0	—	V	I_E = -100μA, I_C = 0
Collector Cutoff Current	I_{CBO}	—	-10	nA μA	V_{CB} = -50V, I_E = 0 V_{CB} = -50V, I_E = 0, T_A = +125°C
Collector Cutoff Current	I_{CEX}	—	-50	nA	V_{CE} = -30V, $V_{EB(off)}$ = -0.5V
Base Cutoff Current	I_{BL}	—	-50	nA	V_{CE} = -30V, $V_{EB(off)}$ = -0.5V
ON CHARACTERISTICS (Note 8)					
DC Current Gain	h_{FE}	75 100 100 100 50	— — — 300 —	—	I_C = -100μA, V_{CE} = -10V I_C = -1.0mA, V_{CE} = -10V I_C = -10mA, V_{CE} = -10V I_C = -150mA, V_{CE} = -10V I_C = -500mA, V_{CE} = -10V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	—	-0.4 -1.6	V	I_C = -150mA, I_B = -15mA I_C = -500mA, I_B = -50mA
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	—	-1.3 -2.6	V	I_C = 150mA, I_B = 15mA I_C = 500mA, I_B = 50mA
SMALL SIGNAL CHARACTERISTICS					
Output Capacitance	C_{obo}	—	8.0	pF	V_{CB} = -10V, f = 1.0MHz, I_E = 0
Input Capacitance	C_{ibo}	—	30	pF	V_{EB} = -2.0V, f = 1.0MHz, I_C = 0
Current Gain-Bandwidth Product	f_T	200	—	MHz	V_{CE} = -20V, I_C = -50mA, f = 100MHz
SWITCHING CHARACTERISTICS					
Turn-On Time	t_{on}	—	45	ns	—
Delay Time	t_d	—	10	ns	V_{CC} = -30V, I_C = -150mA, I_{B1} = -15mA
Rise Time	t_r	—	40	ns	
Turn-Off Time	t_{off}	—	100	ns	—
Storage Time	t_s	—	80	ns	V_{CC} = -6.0V, I_C = -150mA, I_{B1} = I_{B2} = -15mA
Fall Time	t_f	—	30	ns	

Notes: 8. Short duration pulse test used to minimize self-heating effect.




Fig. 3 (2907A) Typical Capacitance





Fig. 4 Typical Collector Saturation Region (2907A Type - PNP)

© Diodes Incorporated

Package Outline Dimensions


Please see AP02002 at http://www.diodes.com/datasheets/ap02002.pdf for latest version.



SOT363			
Dim	**Min**	**Max**	**Typ**
A	0.10	0.30	0.25
B	1.15	1.35	1.30
C	2.00	2.20	2.10
D	0.65 Typ		
F	0.40	0.45	0.425
H	1.80	2.20	2.15
J	0	0.10	0.05
K	0.90	1.00	1.00
L	0.25	0.40	0.30
M	0.10	0.22	0.11
α	0°	8°	-
All Dimensions in mm			

Suggested Pad Layout

Please see AP02001 at http://www.diodes.com/datasheets/ap02001.pdf for the latest version.



Dimensions	Value (in mm)
Z	2.5
G	1.3
X	0.42
Y	0.6
C1	1.9
C2	0.65

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

www.diodes.com