



# Datamate Connectors

## Female Crimp Contacts


- ❖ Spare crimp contacts, for use with L-Tek, J-Tek and Mix-Tek female connectors.
- ❖ For crimp tools see pages 77 to 79.
- ❖ M83 crimp contacts have two additional ident grooves.



### TRIO-TEK




REELED



LOOSE


#### WIRE STRIPPING DETAILS




See page 30 for full connector information.

### L-TEK, J-TEK, MIX-TEK

Large Bore (22 AWG):




Small Bore (24-28 AWG):




SMALL BORE IDENT GROOVE

Extra Small Bore (28-32 AWG):



EXTRA SMALL BORE IDENT GROOVE

#### WIRE STRIPPING DETAILS



See pages 20, 29, 31 to 33, 52 for full connector information.

### HOW TO ORDER

**M8X - XXX 00 XX**

SERIES CODE	
<b>M80</b>	Datamate (pages 20, 29 to 33, 52)
<b>M83</b>	M83 Datamate (pages 70, 71)

FINISH	
<b>01</b>	Gold + Tin (M80-01x)
<b>05</b>	Gold
<b>42</b>	Gold + Tin (M80-2xx)

TYPE			
<b>011</b>	Large Bore for L-Tek, J-Tek, Mix-Tek	<b>254</b>	Reeled 26-28 AWG for Trio-Tek (M80 only)
<b>013</b>	Small Bore for L-Tek, J-Tek, Mix-Tek	<b>283</b>	Loose 22-24 AWG for Trio-Tek (M80 only)
<b>019</b>	Extra Small Bore for L-Tek, J-Tek, Mix-Tek	<b>284</b>	Loose 26-28 AWG for Trio-Tek (M80 only)
<b>253</b>	Reeled 22-24 AWG for Trio-Tek (M80 only)		

All dimensions in mm.

[www.harwin.com](http://www.harwin.com)

