


# Transient Voltage Suppressors Array for ESD Protection

## ESDXXV08S-4C Series

### Description

The ESDXXV08S-4C is in an SO-08 package and may be used to protect two high-speed line pairs. The “flow-thru” design minimizes trace inductance and reduces voltage overshoot associated with ESD events. The low clamping voltage of the ESDXXV08S-4C minimizes the stress on the protected IC.


SO-08



### Feature

- u 500 Watts Peak Pulse Power per Line (tp=8/20µs)
- u Protects four bidirectional I/O lines
- u Low clamping voltage
- u Working voltages : 3.3V, 5V, 12V, 15V and 24V
- u Low leakage current
- u IEC61000-4-2 (ESD) ±15kV (air), ±8kV (contact)
- u IEC61000-4-4 (EFT) 40A (5/50ns)
- u IEC61000-4-5 (Lightning) 12A (8/20µs)

### Functional Diagram



### Applications

- u RS-232, RS-422 & RS-423 Data Lines
- u Audio/Video Inputs
- u Wireless Network Systems
- u Digit Video Interface (DVI)
- u Medical Sensors
- u Notebook Computers

### Mechanical Characteristics

- u JEDEC SO-08 Package
- u Molding Compound Flammability Rating : UL 94V-0
- u Weight 70 Milligrams (Approximate)
- u Quantity Per Reel :3,000pcs
- u Reel Size : 13 inch
- u Lead Finish : Lead Free

### Mechanical Characteristics

Symbol	Parameter	Value	Units	
PPP	Peak Pulse Power (tp=8/20µs waveform)	500	W	
T <sub>L</sub>	Lead Soldering Temperature	260 (10sec)	°C	
T <sub>STG</sub>	Storage Temperature Range	-55 to +150	°C	
T <sub>J</sub>	Operating Temperature Range	-55 to +150	°C	
	IEC61000-4-2 (ESD)	Air Discharge Contact Discharge	±15 ±8	KV
	IEC61000-4-4 (EFT)	40	A	
	IEC61000-4-5 ( Lightning )	12	A	

# Transient Voltage Suppressors Array for ESD Protection

## ESDXXV08S-4C Series

### Electrical Characteristics (@ 25°C Unless Otherwise Specified)

Part Number	Device Marking	V <sub>RWM</sub> (V) (Max.)	V <sub>B</sub> (V) (Min.)	I <sub>T</sub> (mA)	V <sub>C</sub> @5A (Max.)	V <sub>C</sub>		I <sub>R</sub> (μA) (Max.)	C (pF) (Typ.)
						(Max.)	(@A)		
ESD3.3V08S-4C	SMDA 33C	3.3	4.0	1	6.5	10.9	5	75	450
ESD05V08S-4C	SMDA 05C	5.0	6.0	1	9.8	13.5	5	5	300
ESD12V08S-4C	SMDA 12C	12.0	13.3	1	19.0	25.9	5	1	100
ESD15V08S-4C	SMDA 15C	15.0	16.7	1	24.0	30.0	5	1	80
ESD24V08S-4C	SMDA 24C	24.0	26.7	1	43.0	49.0	5	1	50

### Characteristic Curves

Fig1. 8/20μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve



# Transient Voltage Suppressors Array for ESD Protection

## ESDXXV08S-4C Series

### SO-08 Package Outline & Dimensions



DIM	Millimeters		Inches	
	Min	Max	Min	Max
A	4.80	5.00	0.189	0.197
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.053	0.069
D	0.35	0.51	0.013	0.020
G	1.27BSC		0.050BSC	
H	0.10	0.25	0.004	0.010
J	0.19	0.25	0.007	0.010
K	0.40	1.27	0.016	0.050
M	0°	8°	0°	8°
N	0.25	0.50	0.010	0.020
S	5.80	6.20	0.228	0.244

### Soldering Footprint

