



CATALOG LISTING
V3-19M
PAGE 1 OF 1

REPLACES
RELEASE NO. PR-11069

ISSUE
8

REVISIONS

A	CO 82848	
	DCS	15 JUL 96

CHECK

CHECK

CHECK

CHECK

CHECK

CHECK

CHECK

FORMTEK
DRAWN
DCS
15 JUL 96

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CHARACTERISTICS	
OPERATING FORCE	170 - 398 GR MAX 6 - 14 OZ
RELEASE FORCE	113 GR MIN 4 OZ
DIFFERENTIAL TRAVEL	0,15 - 0,41 .006 - .016
OVERTRAVEL	1,01 MIN .040
RELEASE TRAVEL	0,18 MIN .007
FREE POSITION	.625 MAX

ELECTRICAL DATA	
CONTACT ARRANGEMENT S P D T	
L83	15.1A 1/2HP 125, 250 VAC 1/2A 125 VDC, 1/4A 250 VDC 5A 125 VAC "L"

SCALE FULL			
DO NOT SCALE PRINT			
TOLERANCES APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±			
DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
NO PLACES	X 1/04	X X	0,87/03
ONE PLACE	X,X 0,47/018	X X X	0,367/015
TWO PLACES	X,X,X 0,167/008	X X X X	0,137/005
THREE PLACES	X,X,X,X	X X X X X	
SI METRIC <input type="checkbox"/>		US CUSTOMARY <input checked="" type="checkbox"/>	
DESIGN UNITS			
RAW MATERIAL—COMMERCIAL STANDARD MICRO SWITCH STANDARDS APPLY			
DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED			
WEIGHT			

- NOTES
- 1 - LINEAR MEASURE $\frac{mm}{IN}$, OR mm/IN
 - 2 - mm DIMENSIONS ARE FOR REFERENCE ONLY
 - 3 - TERMINALS ARE PLATED FOR SOLDERING
 - 4 - METRIC MOUNTING HOLES

