
CONNOR WINFIELD

THE CONNOR-WINFIELD CORP.
2111 COMPREHENSIVE DRIVE.
AURORA, IL 60505.
FAX (630) 851-5040.
PHONE (630) 851-4722.
www.conwin.com

PRODUCT DATA SHEET

CRYSTAL CONTROLLED OSCILLATORS

SURFACE MOUNT 3.3V PECL CLOCK



EML5213

ABSOLUTE MAXIMUM RATINGS — TABLE 1.0

PARAMETER	UNITS	MINIMUM	NOMINAL	MAXIMUM	UNITS	NOTE
Storage Temperature		-55	-	125	°C	
Supply Voltage	(Vcc)	-0.5	-	7.0	Vdc	

OPERATING SPECIFICATIONS — TABLE 2.0

PARAMETER		MINIMUM	NOMINAL	MAXIMUM	UNITS	NOTE
Center Frequency	(Fo)	19.44	-	164	MHz	
Total Frequency Tolerance		-50	-	50	ppm	1
Operating Temperature Range		0	-	70	°C	
Supply Voltage	(Vcc)	3.135	3.3	3.465	Vdc	
Supply Current	(Icc)	-	-	60	mA	
Jitter (BW=10Hz to 20MHz)		-	-	5	ps rms	
Jitter (BW=12kHz to 20MHz)		-	-	1	ps rms	
SSB Phase Noise at 10Hz offset		-	-60	-	dBc/Hz	
SSB Phase Noise at 100Hz offset		-	-90	-	dBc/Hz	
SSB Phase Noise at 1KHz offset		-	-100	-	dBc/Hz	
SSB Phase Noise at 10KHz offset		-	-125	-	dBc/Hz	
SSB Phase Noise at 10KHz offset		-	-135	-	dBc/Hz	

PECL OUTPUT CHARACTERISTICS — TABLE 3.0

PARAMETER		MINIMUM	NOMINAL	MAXIMUM	UNITS	NOTE
LOAD		-	-	50	Ohms	2
Voltage (High)	(Voh)	2.275	-	-	Vdc	
(Low)	(Vol)	-	-	1.68	Vdc	
Duty Cycle		45	50	55	%	3
Rise / Fall Time 20% to 80%		-	-	1	nS	

PACKAGE CHARACTERISTICS — TABLE 4.0

Package	Hermetically sealed, leadless ceramic package.

Notes
1) Includes calibration, stability vs. temperature, supply and load variations, shock, vibration and aging (10 years).
2) Output must be terminated into 50 ohms to Vcc – 2V or Thevenin equivalent.
3) Duty Cycle measured at 1.977V

DESCRIPTION

The Connor-Winfield EML5213 is a fixed frequency surface mount Crystal Controlled Oscillator (XO) designed for applications requiring low jitter and tight Frequency stability. Operating at 3.3V supply voltage, the EML5213 provides LVPECL compatible outputs.

FEATURES

3.3V OPERATION

LVPECL DIFFERENTIAL OUTPUTS

LOW JITTER <1pS RMS

OVERALL FREQUENCY TOLERANCE: ±50ppm

TEMPERATURE RANGE: 0 to 70°C

SURFACE MOUNT PACKAGE

TAPE AND REEL PACKAGING

ORDERING INFORMATION

EML5213 - 156.25MHz

EML5213: PECL SERIES
156.25MHz: CENTER FREQUENCY


Specifications subject to change without notice.

©Copyright 2001 Connor-Winfield all rights reserved.

CONNOR WINFIELD
THE CONNOR-WINFIELD CORP.
2111 COMPREHENSIVE DRIVE.
AURORA, IL 60505.
FAX (630) 851-5040.
PHONE (630) 851-4722.
www.conwin.com

PRODUCT DATA SHEET


CRYSTAL CONTROLLED OSCILLATORS




PIN	CONNECTION
1	$\overline{Q}$ OUTPUT
2	N/C
3	GND
4	Q OUTPUT
5	N/C
6	Vcc

NOTE 1: Metal cover is tied to pin 3


OUTPUT WAVEFORM



NO LEADS SUGGESTED PAD LAYOUT



TEST CIRCUIT



©Copyright 2001 Connor-Winfield all rights reserved.