NTGS3455T1

MOSFET
-3.5 Amps, -30 Volts

P−Channel TSOP−6

ON Semiconductor®

http://onsemi.com

$V_{(BR)DSS}$	$R_{DS(on)}$ TYP	I_D Max
−30 V	100 mΩ @ −10 V	−3.5 A


Features

- Ultra Low $R_{DS(on)}$
- Higher Efficiency Extending Battery Life
- Miniature TSOP−6 Surface Mount Package
- Pb−Free Package is Available

Applications

- Power Management in Portable and Battery−Powered Products, i.e.: Cellular and Cordless Telephones, and PCMCIA Cards

P−Channel



MAXIMUM RATINGS (T_J = 25°C unless otherwise noted.)

Rating	Symbol	Value	Unit
Drain−to−Source Voltage	V_{DSS}	−30	Volts
Gate−to−Source Voltage − Continuous	V_{GS}	±20.0	Volts
Thermal Resistance Junction−to−Ambient (Note 1)	$R_{\theta JA}$	62.5	°C/W
Total Power Dissipation @ T_A = 25°C	P_d	2.0	Watts
Drain Current − Continuous @ T_A = 25°C	I_D	−3.5	Amps
− Pulsed Drain Current (T_p < 10 μS)	I_{DM}	−20	Amps
Maximum Operating Power Dissipation	P_d	1.0	Watts
Maximum Operating Drain Current	I_D	−2.5	Amps
Thermal Resistance Junction−to−Ambient (Note 2)	$R_{\theta JA}$	128	°C/W
Total Power Dissipation @ T_A = 25°C	P_d	1.0	Watts
Drain Current − Continuous @ T_A = 25°C	I_D	−2.5	Amps
− Pulsed Drain Current (T_p < 10 μS)	I_{DM}	−14	Amps
Maximum Operating Power Dissipation	P_d	0.5	Watts
Maximum Operating Drain Current	I_D	−1.75	Amps
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to 150	°C
Maximum Lead Temperature for Soldering Purposes for 10 Seconds	T_L	260	°C


Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. Mounted onto a 2″ square FR−4 board (1 in sq, 2 oz. Cu. 0.06″ thick single sided), t < 5.0 seconds.
2. Mounted onto a 2″ square FR−4 board (1 in sq, 2 oz. Cu. 0.06″ thick single sided), operating to steady state.

MARKING DIAGRAM & PIN ASSIGNMENT



TSOP−6
CASE 318G
STYLE 1



455 = Specific Device Code
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation may vary depending upon manufacturing location.

ORDERING INFORMATION

Device	Package	Shipping†
NTGS3455T1	TSOP−6	3000 Tape & Reel
NTGS3455T1G	TSOP−6 (Pb−Free)	3000 Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2007

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Notes 3 & 4)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−Source Breakdown Voltage (V_{GS} = 0 Vdc, I_D = −10 μA)		$V_{(BR)DSS}$	−30	–	–	Vdc
Zero Gate Voltage Drain Current (V_{GS} = 0 Vdc, V_{DS} = −30 Vdc, T_J = 25°C) (V_{GS} = 0 Vdc, V_{DS} = −30 Vdc, T_J = 70°C)		I_{DSS}	– –	– –	−1.0 −5.0	μAdc
Gate−Body Leakage Current (V_{GS} = −20.0 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	–	–	−100	nAdc
Gate−Body Leakage Current (V_{GS} = +20.0 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	–	–	100	nAdc
ON CHARACTERISTICS						
Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = −250 μAdc)		$V_{GS(th)}$	−1.0	−1.87	−3.0	Vdc
Static Drain−Source On−State Resistance (V_{GS} = −10 Vdc, I_D = −3.5 Adc) (V_{GS} = −4.5 Vdc, I_D = −2.7 Adc)		$R_{DS(on)}$	– –	0.094 0.144	0.100 0.170	Ω
Forward Transconductance (V_{DS} = −15 Vdc, I_D = −3.5 Adc)		g_{FS}	–	6.0	–	mhos
DYNAMIC CHARACTERISTICS						
Total Gate Charge	(V_{DS} = −15 Vdc, V_{GS} = −10 Vdc, I_D = −3.5 Adc)	Q_{tot}	–	9.0	13	nC
Gate−Source Charge		Q_{gs}	–	2.5	–	
Gate−Drain Charge		Q_{gd}	–	2.0	–	
Input Capacitance	(V_{DS} = −5.0 Vdc, V_{GS} = 0 Vdc, f = 1.0 MHz)	C_{iss}	–	480	–	pF
Output Capacitance		C_{oss}	–	220	–	
Reverse Transfer Capacitance		C_{rss}	–	60	–	
SWITCHING CHARACTERISTICS						
Turn−On Delay Time	(V_{DD} = −20 Vdc, I_D = −1.0 Adc, V_{GS} = −10 Vdc, R_g = 6.0 Ω)	$t_{d(on)}$	–	10	20	ns
Rise Time		t_r	–	15	30	
Turn−Off Delay Time		$t_{d(off)}$	–	20	35	
Fall Time		t_f	–	10	20	
Reverse Recovery Time	(I_S = −1.7 Adc, dI_S/dt = 100 A/μs)	t_{rr}	–	30	–	ns
BODY−DRAIN DIODE RATINGS						
Diode Forward On−Voltage	(I_S = −1.7 Adc, V_{GS} = 0 Vdc)	V_{SD}	–	−0.90	−1.2	Vdc
Diode Forward On−Voltage	(I_S = −3.5 Adc, V_{GS} = 0 Vdc)	V_{SD}	–	−1.0	–	Vdc

3. Indicates Pulse Test: P.W. = 300 μsec max, Duty Cycle = 2%.
4. Class 1 ESD rated − Handling precautions to protect against electrostatic discharge are mandatory.




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate−to−Source Voltage




Figure 4. On−Resistance vs. Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Capacitance Variation




Figure 7. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge




Figure 8. Diode Forward Voltage vs. Current




Figure 9. Normalized Thermal Transient Impedance, Junction−to−Ambient





Figure 10. Single Pulse Power

PACKAGE DIMENSIONS

TSOP−6
CASE 318G−02
ISSUE P




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.90	1.00	1.10	0.035	0.039	0.043
A1	0.01	0.06	0.10	0.001	0.002	0.004
b	0.25	0.38	0.50	0.010	0.014	0.020
c	0.10	0.18	0.26	0.004	0.007	0.010
D	2.90	3.00	3.10	0.114	0.118	0.122
E	1.30	1.50	1.70	0.051	0.059	0.067
e	0.85	0.95	1.05	0.034	0.037	0.041
L	0.20	0.40	0.60	0.008	0.016	0.024
H_E	2.50	2.75	3.00	0.099	0.108	0.118
θ	0°	–	10°	0°	–	10°

STYLE 1:
PIN 1. DRAIN
2. DRAIN
3. GATE
4. SOURCE
5. DRAIN
6. DRAIN

SOLDERING FOOTPRINT*



*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative