

FQB020ADC-007-S<sup>New</sup>

Product



<b>Sales Region</b>	Worldwide (except Japan)
<b>Power Supply</b>	DC
<b>Series</b>	FQB
<b>Status</b>	Production
<b>Features</b>	MIL-STD-461
	MIL-STD-1275
	MIL-STD-704
	RTCA DO-160
<b>Option</b>	Flanged baseplate
	Standard screening
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	
<b>Brand</b>	TDK-Lambda



### Electrical Characteristics

Rated Current	20A
Rated Voltage [AC]	
Rated Voltage [DC]	40V
Withstanding Voltage	DC2250V, 60s [terminals - case]
Insulation Resistance (Min.)	
Leakage Current (Max.)	
DC Resistance (Max.)	25mΩ
Common Mode Attenuation (Min.)	30dB
Differential Mode Attenuation (Min.)	50dB

### Package Type & Size

Package / Mounting	Low profile
	PCB
Length(L)	60.6mm Nom. (2.39in Nom.)
Width(W)	55.9mm Nom. (2.20in Nom.)
Height(H)	12.7mm Nom. (0.50in Nom.)
Weight	100g Typ.

### Other

Terminals	Pin
Operating Temp. Range	-40 to 115°C
Performance	Wide range high attenuation
Function	

