


Surface Mount Zener Diodes

Features:


- * 500mw Power Dissipation
- * Ideal for Surface Mount Application
- * Zener Breakdown Voltage Range 2.4V to 51V
- * Pb-Free package is available
- * ESD Rating of Class 3 (>16kV) per Human Body Model
- * AEC-Q101 qualified

Mechanical Data:

- * Case : SOD-123 Molded plastic
- * Terminals: Solderable per MIL-STD-202, Method 208
- * Polarity: Cathode Indicated by Polarity Band
- * Marking: Marking Code (See Table on Page 2)
- * Weigh: 0.01grams(approx)



Equivalent Circuit Diagram



Maximum Ratings and Electrical Characteristics (Ta=25°C Unless Otherwise Noted)

Characteristics	Symbol	Value	Unit
Total Power Dissipation on FR-5 Board ⁽¹⁾	PD	500	mW
Thermal Resistance Junction to Ambient Air ⁽¹⁾	R ^θ JA	305	°C/W
Forward Voltage @ IF=10mA	VF	0.9	V
Junction and Storage Temperature Range	Tj,TSTG	-55 to +150	°C

NOTES:

1. Device mounted on ceramic PCB; 7.6mm × 9.4mm × 0.87mm with pad areas 25mm²

Ratings and Characteristic curves




FIG. 1 Power Dissipation vs Ambient temperature



FDZD2.4 ~ FDZD51



Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted, $V_F=0.9\text{V Max@ } I_F=10\text{mA}$)

Device	Device Marking (2)	Zener Voltage Range (1)				Maximum Zener Impedance(3)			Maximum Reverse Current		Typical Temperature Coefficient @ I _{ZT} mV/°C		Test Current I _{ZTC}
		V _Z @ I _{ZT}			@ I _{ZT}	Z _{ZT} @ I _{ZT}	Z _{ZK} @ I _{ZK}	I _{zk}	I _R	@ V _R			
		Nom(V)	Min(V)	Max(V)	mA	Ω		mA	μA	V	Min	Max	mA
FDZD2.4	WX	2.4	2.2	2.6	5	100	600	1.0	50	1.0	-3.5	0	5
FDZD2.7	W1	2.7	2.5	2.9	5	100	600	1.0	20	1.0	-3.5	0	5
FDZD3.0	W2	3.0	2.8	3.2	5	95	600	1.0	10	1.0	-3.5	0	5
FDZD3.3	W3	3.3	3.1	3.5	5	95	600	1.0	5.0	1.0	-3.5	0	5
FDZD3.6	W4	3.6	3.4	3.8	5	90	600	1.0	5.0	1.0	-3.5	0	5
FDZD3.9	W5	3.9	3.7	4.1	5	90	600	1.0	3.0	1.0	-3.5	0	5
FDZD4.3	W6	4.3	4.0	4.6	5	90	600	1.0	3.0	1.0	-3.5	0	5
FDZD4.7	W7	4.7	4.4	5.0	5	80	500	1.0	3.0	2.0	-3.5	0.2	5
FDZD5.1	W8	5.1	4.8	5.4	5	60	480	1.0	2.0	2.0	-2.7	1.2	5
FDZD5.6	W9	5.6	5.2	6.0	5	40	400	1.0	1.0	2.0	-2.0	2.5	5
FDZD6.2	WA	6.2	5.8	6.6	5	10	150	1.0	3.0	4.0	0.4	3.7	5
FDZD6.8	WB	6.8	6.4	7.2	5	15	80	1.0	2.0	4.0	1.2	4.5	5
FDZD7.5	WC	7.5	7.0	7.9	5	15	80	1.0	1.0	5.0	2.5	5.3	5
FDZD8.2	WD	8.2	7.7	8.7	5	15	80	1.0	0.7	5.0	3.2	6.2	5
FDZD9.1	WE	9.1	8.5	9.6	5	15	100	1.0	0.5	6.0	3.8	7.0	5
FDZD10	WF	10	9.4	10.6	5	20	150	1.0	0.2	7.0	4.5	8.0	5
FDZD11	WG	11	10.4	11.6	5	20	150	1.0	0.1	8.0	5.4	9.0	5
FDZD12	WH	12	11.4	12.7	5	25	150	1.0	0.1	8.0	6.0	10.0	5
FDZD13	WI	13	12.4	14.1	5	30	170	1.0	0.1	8.0	7.0	11.0	5
FDZD15	WJ	15	13.8	15.8	5	30	200	1.0	0.1	10.5	9.2	13.0	5
FDZD16	WK	16	15.3	17.1	5	40	200	1.0	0.1	11.2	10.4	14.0	5
FDZD18	WL	18	16.8	19.1	5	45	225	1.0	0.1	12.6	12.4	16.0	5
FDZD20	WM	20	18.8	21.2	5	55	225	1.0	0.1	14.0	14.4	18.0	5
FDZD22	WN	22	20.8	23.3	5	55	250	1.0	0.1	15.4	16.4	20.0	5
FDZD24	WO	24	22.8	25.6	5	70	250	1.0	0.1	16.8	18.4	22.0	5
FDZD27	WP	27	25.1	28.9	2	80	300	0.5	0.1	18.9	21.4	25.3	2
FDZD30	WQ	30	28.0	32	2	80	300	0.5	0.1	21.0	24.4	29.4	2
FDZD33	WR	33	31.0	35	2	80	325	0.5	0.1	23.1	27.4	33.4	2
FDZD36	WS	36	34.0	38	2	90	350	0.5	0.1	25.2	30.4	37.4	2
FDZD39	WT	39	37.0	41	2	130	350	0.5	0.1	27.3	33.4	41.2	2
FDZD43	WU	43	40.0	46	2	100	700	1.0	0.1	32	10.0	12.0	5
FDZD47	WV	47	44.0	50	2	100	750	1.0	0.1	35	10.0	12.0	5
FDZD51	WW	51	48.0	54	2	100	750	1.0	0.1	38	10.0	12.0	5

Note:

1. Tested with pulses, period = 5ms, pulse width = 300us.
2. When provided, otherwise, parts are provided with date code only, and type number identifications appears on reel only.
3. $f=1\text{KHz}$.

SOD-123




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.94	1.17	1.35	0.037	0.046	0.053
A1	0.00	0.05	0.10	0.000	0.002	0.004
b	0.51	0.61	0.71	0.020	0.024	0.028
c	---	---	0.15	---	---	0.006
D	1.40	1.60	1.80	0.055	0.063	0.071
E	2.54	2.69	2.84	0.100	0.106	0.112
H _E	3.56	3.68	3.86	0.140	0.145	0.152
L	0.25	---	---	0.010	---	---

STYLE 1:
PIN 1. CATHODE
2. ANODE

SOLDERING FOOTPRINT*



SCALE 10:1 $\left(\frac{\text{mm}}{\text{inches}} \right)$