



P-Channel 200-V (D-S) MOSFET


PRODUCT SUMMARY			
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)	Q_g (Typ)
-200	2.35 @ $V_{GS} = -10$ V	-0.49	8.0
	2.45 @ $V_{GS} = -6.0$ V	-0.48	

FEATURES

- TrenchFET® Power MOSFET
- Ultra Low On-Resistance
- Small Size

APPLICATIONS

- Active Clamp Circuits in DC/DC Power Supplies



Ordering Information: Si2327DS -T1—E3

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)					
Parameter	Symbol	5 sec	Steady State	Unit	
Drain-Source Voltage	V_{DS}	-200		V	
Gate-Source Voltage	V_{GS}	± 20			
Continuous Drain Current ($T_J = 150^\circ\text{C}$) ^{a, b}	I_D	$T_A = 25^\circ\text{C}$	-0.49	-0.38	A
		$T_A = 70^\circ\text{C}$	-0.39	-0.31	
Pulsed Drain Current	I_{DM}	-1.0			
Continuous Source Current (Diode Conduction) ^{a, b}	I_S	-1.0	-0.6		
Single-Pulse Avalanche Current	I_{AS}	L = 1.0 mH	4.0		
Single-Pulse Avalanche Energy			E_{AS}	0.8	
Maximum Power Dissipation ^{a, b}	P_D	$T_A = 25^\circ\text{C}$	1.25	0.75	W
		$T_A = 70^\circ\text{C}$	0.8	0.48	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150		$^\circ\text{C}$	

THERMAL RESISTANCE RATINGS					
Parameter	Symbol	Typical	Maximum	Unit	
Maximum Junction-to-Ambient ^a	R_{thJA}	$t \leq 5$ sec	75	100	$^\circ\text{C/W}$
		Steady State	120	166	
Maximum Junction-to-Foot (Drain)	R_{thJF}	40	50		

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
b. Pulse width limited by maximum junction temperature.

SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Conditions	Limits			Unit
			Min	Typ	Max	
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -250 μA	-200			V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-2.5		-4.5	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -200 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -200 V, V _{GS} = 0 V, T _J = 55 °C			-10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≤ -15 V, V _{GS} = 10 V	-1.0			A
Drain-Source On-Resistance ^a	r _{DS(on)}	V _{GS} = -10 V, I _D = -0.5 A		1.9	2.35	Ω
		V _{GS} = -6.0 V, I _D = -0.5 A		1.96	2.45	
Forward Transconductance ^a	g _{fs}	V _{DS} = -15 V, I _D = -0.5 A		1.8		S
Diode Forward Voltage	V _{SD}	I _S = -1.0 A, V _{GS} = 0 V		0.85	-1.2	V
Dynamic^b						
Total Gate Charge	Q _g	V _{DS} = -100 V, V _{GS} = 10 V I _D ≅ -0.5 A		8.0	12	nC
Gate-Source Charge	Q _{gs}			1.3		
Gate-Drain Charge	Q _{gd}			2.5		
Gate Resistance	R _g	f = 1.0 MHz		8.0		Ω
Input Capacitance	C _{iss}	V _{DS} = -25 V, V _{GS} = 0, f = 1 MHz		340	510	pF
Output Capacitance	C _{oss}			25		
Reverse Transfer Capacitance	C _{rss}			14		
Switching^c						
Turn-On Time	t _{d(on)}	V _{DD} = -100 V, R _L = 100 Ω I _D ≅ -1.0 A, V _{GEN} = -10 V R _g = 6 Ω		8	12	ns
	t _r			11	17	
Turn-Off Time	t _{d(off)}			16	25	
	t _f			11	17	
Body Diode Reverse Recovery Charge	Q _{rr}	I _F = 0.5 A, di/dt = 100 A/μs		140	200	nC







Notes

- a. Pulse test: PW ≤ 300 μs duty cycle ≤ 2%.
b. For DESIGN AID ONLY, not subject to production testing.
c. Switching time is essentially independent of operating temperature.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.








TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73240>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.