


Features

- $R_{DS(ON)} < 0.80\Omega$ @ $V_{GS} = 10V$
- Fast switching capability
- Low gate charge
- Lead free in compliance with EU RoHS directive.
- Green molding compound

Mechanical Data

- Case: TO-220, ITO-220, TO-262, TO-263 Package




Pin Definition:
 1. Gate
 2. Drain
 3. Source

Ordering Information

Part No.	Package	Packing
12N60T	TO-220	50pcs / Tube
12N60F	ITO-220	50pcs / Tube
12N60K	TO-262	50pcs / Tube
12N60G	TO-263	50pcs / Tube

Block Diagram



Maximum Ratings $T_A = 25^\circ C$ unless otherwise specified

PARAMETER	SYMBOL	RATINGS	UNIT	
Drain-Source Voltage	V_{DSS}	600	V	
Gate-Source Voltage	V_{GSS}	± 30	V	
Continuous Drain Current	I_D	12	A	
Pulsed Drain Current (Note 2)	I_{DM}	48	A	
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	790	mJ
Power Dissipation	TO-220/TO-262/TO-263	P_D	225	W
	ITO-220		51	W
Junction Temperature	T_J	+150	$^\circ C$	
Operating Temperature	T_{OPR}	-55 ~ +150	$^\circ C$	
Storage Temperature	T_{STG}	-55 ~ +150	$^\circ C$	

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating : Pulse width limited by T_J

3. $L = 30mH$, $I_{AS} = 7.1A$, $V_{DD} = 50V$, $R_G = 25\Omega$, Starting $T_J = 25^\circ C$



THERMAL DATA



PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/ITO-220 TO-262/TO-263	θ_{JA}	62.5	$^{\circ}\text{C/W}$
Junction to Case	TO-220/TO-262/TO-263	θ_{JC}	0.56	$^{\circ}\text{C/W}$
	ITO-220		2.6	







ELECTRICAL CHARACTERISTICS ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$V_{GS}=0\text{V}, I_D=250\mu\text{A}$	600			V
Drain-Source Leakage Current		I_{DSS}	$V_{DS}=600\text{V}, V_{GS}=0\text{V}$			1	μA
Gate- Source Leakage Current	Forward	I_{GSS}	$V_{GS}=30\text{V}, V_{DS}=0\text{V}$			100	nA
	Reverse		$V_{GS}=-30\text{V}, V_{DS}=0\text{V}$			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2.0		4.0	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS}=10\text{V}, I_D=6\text{A}$		0.60	0.80	Ω
DYNAMIC CHARACTERISTICS							
Input Capacitance		C_{ISS}	$V_{DS}=25\text{V}, V_{GS}=0\text{V}, f=1.0\text{MHz}$		1480		pF
Output Capacitance		C_{OSS}			200		pF
Reverse Transfer Capacitance		C_{RSS}			25		pF
SWITCHING CHARACTERISTICS							
Turn-On Delay Time		$t_{D(ON)}$	$V_{DD}=300\text{V}, I_D=12\text{A},$ $R_G=25\Omega$ (Note 1, 2)		30		ns
Turn-On Rise Time		t_R			115		ns
Turn-Off Delay Time		$t_{D(OFF)}$			95		ns
Turn-Off Fall Time		t_F			85		ns
Total Gate Charge		Q_G	$V_{DS}=480\text{V}, I_D=12\text{A},$ $V_{GS}=10\text{V}$ (Note 1, 2)		42		nC
Gate-Source Charge		Q_{GS}			8.6		nC
Gate-Drain Charge		Q_{GD}			21		nC
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS							
Drain-Source Diode Forward Voltage		V_{SD}	$V_{GS}=0\text{V}, I_S=12\text{A}$			1.4	V
Maximum Continuous Drain-Source Diode Forward Current		I_S				12	A
Maximum Pulsed Drain-Source Diode Forward Current		I_{SM}				48	A
Reverse Recovery Time		t_{rr}	$V_{GS}=0\text{V}, I_S=12\text{A},$		570		ns
Reverse Recovery Charge		Q_{RR}	$di/dt=100\text{A}/\mu\text{s}$ (Note 1)		5.5		μC

Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.







2. Essentially independent of operating temperature.

TEST CIRCUITS AND WAVEFORMS

Peak Diode Recovery dv/dt Test Circuit

Peak Diode Recovery dv/dt Waveforms



TEST CIRCUITS AND WAVEFORMS(Cont.)

Switching Test Circuit

Switching Waveforms

Gate Charge Test Circuit

Gate Charge Waveform

Unclamped Inductive Switching Test Circuit

Unclamped Inductive Switching Waveforms




TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS




TO-220 Mechanical Drawing



TO-220AB		
Unit:mm		
DIM	MIN	MAX
A	14.80	15.80
B	9.57	10.57
C	2.54	2.94
D	5.80	6.80
E	2.95	3.95
F	12.70	13.40
G	2.34	2.74
H	0.51	1.11
I	0.97	1.57
J	3.54 ϕ	4.14 ϕ
K	4.27	4.87
L	1.07	1.47
M	2.03	2.92
N	0.30	0.64

ITO-220 Mechanical Drawing



ITO-220AB		
Unit:mm		
DIM	MIN	MAX
A	14.50	15.50
B	9.50	10.50
C	2.50	2.90
D	6.30	7.30
E	3.30	4.30
F	13.00	14.00
G	2.35	2.75
H	0.30	0.90
I	0.90	1.50
J	3.20	3.80
K	4.24	4.84
L	2.52	2.92
M	1.09	1.49
N	0.47	0.64

