## Accessories

### TW Series Accessories

| Appearance | | Description/Usage | | Part Number |
|---|---|---|---|---|
| Lamp Removal Tool |  | Rubber tool used to install or remove LED's and incandescent lamps | | OR-55 |
| Contact Block Remover |  | Used to remove contact blocks, transformers, lenses, and adaptors. Can also be used to determine panel thickness adjustment. | | TW-KC1 |
| Nut Locking Wrench |  | Used in OR-14 locking wrench to tighten locking nuts inside square bezel | | TW-KQ2 |
| Metal Bezel |  | Chrome plated bezels tighten onto operator (replacement for damaged bezels) | Standard octagonal units (chrome-pl.) | AW-R8 |
| | | | Full shroud octagonal units (chrome-pl.) | AW-RF8 |
| | | | Full shroud mushroom head units Ø 40mm | AW-G4 |
| Plastic Bezel |  | Black plastic bezels for square buttons (replacement for damaged bezels) | Round flush units (black plastic) | AW-RP1B |
| | | | Round extended units (black plastic) | AW-FP1B |
| | | | Square units (black plastic) | AW-Q1B |
| | | | Square units with full shroud (black plastic) | AW-QF1B |
| Boot/Cover |  | Used to cover and protect pushbuttons | Waterproof lens cover for square pilot lights | APW00LN |
| | | | Waterproof lens cover for square illuminated buttons | APW00L |
| | | | Clear boot for round flush units | OC-31 |
| | | | Clear boot for round extended units | OC-32 |
| | | | *In place of asterisk, specify **Rubber Boot** color: **B** (black), **G** (green), **R** (red), **Y** (yellow) - (nitril rubber) | OCW-11* |
| Anti-Rotation Ring |  | Ring to prevent operator base from rotating in the mounting hole. Used when nameplate is not used | | OGL-31 |
| Mounting Hole Plug |  | Black rubber plug fills unused mounting holes in panel. | | OB-31 |
| Metallic Mounting Hole Plug |  | For plugging unused mounting holes in the panel. Tighten the attached locking ring to a torque of 12 kfg-cm maximum<br>Degree of protection: IP66 | | LW9Z-BM |
| Replacement Keys |  | Pair of keys (#0) | | TW-SK |
| Replacement Black Sleeve for Keyswitch |  | | | AKW2B-B |
| Metal Button Guard |  | Used on flush buttons to prevent inadvertent actuation | | OLW-C |