

SANYO	No.2816A	2SC4221
		NPN Triple Diffused Planar Silicon Transistor
Switching Regulator Applications		

Features

- . High breakdown voltage, high reliability
- . Fast switching speed (t_f : 0.1us typ)
- . Wide ASO
- . Adoption of MBIT process
- . Suitable for sets whose height is restricted

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

			unit
Collector to Base Voltage	V_{CB0}	800	V
Collector to Emitter Voltage	V_{CE0}	500	V
Emitter to Base Voltage	V_{EB0}	7	V
Collector Current	I_C	3	A
Peak Collector Current	i_{cp} $PW \leq 300\mu s, \text{duty cycle} \leq 10\%$	6	A
Base Current	I_B	1	A
Allowable Power Dissipation	P_C $T_c=25^\circ\text{C}$	40	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics at $T_a=25^\circ\text{C}$


		min	typ	max	unit
Collector Cutoff Current	I_{CB0} $V_{CB}=500V, I_E=0$			10	μA
Emitter Cutoff Current	I_{EB0} $V_{EB}=5V, I_C=0$			10	μA
DC Current Gain	$h_{FE(1)}$ * $V_{CE}=5V, I_C=0.3A$	15		50	
	$h_{FE(2)}$ $V_{CE}=5V, I_C=1.5A$	8			
C-E Saturation Voltage	$V_{CE(sat)}$ $I_C=1.5A, I_B=0.3A$			1.0	V
B-E Saturation Voltage	$V_{BE(sat)}$ $I_C=1.5A, I_B=0.3A$			1.5	V
Gain-Bandwidth Product	f_T $V_{CE}=10V, I_C=0.3A$		18		MHz
Output Capacitance	c_{ob} $V_{CB}=10V, f=1\text{MHz}$		50		pF

Continued on next page.


*:The $h_{FE(1)}$ of the 2SC4221 is classified as follows. When specifying the $h_{FE(1)}$ rank, specify two ranks or more.

15	L	30	20	M	40	30	N	50
----	---	----	----	---	----	----	---	----

Switching Time Test Circuit









Package Dimensions 2049A (unit: mm)







E. Emitter
C. Collector
B. Base

Continued from preceding page.

			min	typ	max	unit
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C=1mA, I_E=0$	800			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C=5mA, R_{BE}=\infty$	500			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E=1mA, I_C=0$	7			V
C-E Sustain Voltage	$V_{CEX(sus)}$	$I_C=1.5A, I_{B1}=0.6A$ $L=2mH, I_{B2}=-0.6A, \text{clamped}$	500			V
Turn-ON Time	t_{on}	$I_C=2A, I_{B1}=0.4A$ $I_{B2}=-0.8A, R_L=100\text{ohms}$ $V_{CC}=200V$		0.5		μs
Storage Time	t_{stg}			3.0		μs
Fall Time	t_f			0.3		μs





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.