



## ZWS150BAF-24/FV





| Sales Region           | Worldwide                      |
|------------------------|--------------------------------|
| Series                 | ZWS-BAF                        |
| Status                 | Production                     |
| Feature                |                                |
| Option                 | Without output voltage trimmer |
| Option Lineup          | Please refer to here.          |
| Recommended EMC Filter | Please refer to here.          |
| Accessories            | Please refer to the catalog    |



| Electrical Characteristics |             |  |
|----------------------------|-------------|--|
| Input Voltage Range[AC]    | 85 to 265V  |  |
| Input Voltage Range[DC]    | 120 to 370V |  |
| Efficiency                 | 90% Typ.    |  |
| Rated Output Voltage[DC]   | 24V         |  |
| Output Voltage Range[DC]   | Fixed       |  |
| Maximum Output Current     | 6.3A        |  |
| Maximum Output Power       | 151.2W      |  |

| Cases Shape & Size |            |
|--------------------|------------|
| Case' shape        | PC board   |
| Width(W)           | 75mm Nom.  |
| Height(H)          | 37mm Nom.  |
| Depth(D)           | 160mm Nom. |
| Weight             | 390g Typ.  |

| Other  |  |  |
|--|--|--|
| -10 to 70°C  |  |  |
| Convection cooling   |  |  |
| UL60950-1  |  |  |
| CSA C22.2 No.60950-1   |  |  |
| EN60950-1  |  |  |
| EN50178 (OV II)  |  |  |
| Den-an   |  |  |
| This page only shows representative characteristics. Please refer to the |  |  |
| technical data for detailed specifications and conditions.               |  |  |
|  |  |  |

<sup>!</sup> Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.