



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)		
	A	B	C
PHB-2*2A	2.00	6.00	3.00
PHB-2*3A	4.00	8.00	3.00
PHB-2*4A	6.00	10.00	3.00
PHB-2*5A	8.00	12.00	5.00
PHB-2*6A	10.00	14.00	7.00
PHB-2*7A	12.00	16.00	9.00
PHB-2*8A	14.00	18.00	11.00
PHB-2*9A	16.00	20.00	13.00
PHB-2*10A	18.00	22.00	15.00
PHB-2*11A	20.00	24.00	17.00
PHB-2*12A	22.00	26.00	19.00
PHB-2*13A	24.00	28.00	21.00
PHB-2*14A	26.00	30.00	23.00
PHB-2*22A	42.00	46.00	39.00

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	PHB-2*NA		版本 REV.	A
			$X \pm 0.25$	$X' \pm 2'$		2013、07、01		品名 TITLE	PHB直针 WAFER DIP TYPE		页次 SHEET	1/1
			$X \pm 0.20$	$X' \pm 1'$	审核 CHECK	2013、07、03		客户料号 CUTM. NO.				
			$.XX \pm 0.15$	$.XX' \pm 0.5'$	核准 APPROVAL	2013、07、05						
			$.XXX \pm 0.10$	$.XXX' \pm 0.5'$	单位 UNITS	MM	比例 SCALE	1:1		乐清市博穆电子有限公司		