



E243711 (ULJ) SPT-2 2×18AWG(0.82mm²) VW-1 105°C 300V CSA 228191 SPT-2
 2×18AWG(0.82mm²) FT2 105°C 300V JINLIANLI-LJ-

NO.	SPECIFICATION	COLOUR	MATERIAL	AMOUNT
①	Non-polar terminal 98661	Silver	Cu	2P
②	Model aircraft 8661AN-2P	WHITE	PBT	1PCS
③	Plug JLL-101	BLACK	PVC Cu	1PCS
④	Wire SPT-2 18AWG/2C 105°C	BLACK	PVC Cu	1PCS
⑤	terminal 98715	Silver	Cu	3P
⑥	Model aircraft 8714P	WHITE	PBT	1PCS
⑦	Couplers JLL-204	BLACK	PVC Cu	1PCS
⑧	Ties	BLACK		1PCS

TESTING:
 1) 100% OPEN & SHORT TESTING
 2) INSULATION RESISTANCE: 100M ohm(min)
 3) VOLTAGE: DC500V/1min
 4) ROHS COMPLIANT

CONDUCTOR CONSTRUCTION(N/mm):
 41/0.16AS
 PVC JACKET AVERAGE THICKNESS: 1.14mm
 00: 3.6±0.15*7.0±0.2mm



Scale	1:1							Name	Item No.
TOLERANCE								Miller	A-PC2201-030042-2
X.X	±0.40					Drawn	3/23/12	Warner	
X.XX	±0.25					Approved	3/23/12		Title
X.XXX	±0.15								SPT-2#18*2C 105C
Angle	±3°								Drawing No.
									rev00
									Sheet



Modification Date Name

Replace Sheet