
Creation Date : September 17, 2020 (GMT)

AC-DC Power Supplies

XMS5008H

RoHS

Sales Region	Worldwide (except Japan)
Series	XMS
Model	XMS500
Status	Production
Feature	Medical for Medical instruments 2MOPP 2MOPP
Options	Class II input Fan supply
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	
Efficiency	92% Typ.
Rated Output Voltage[DC]	24Vdc
Output Voltage Range[DC]	
Maximum Output Current	20.8A
Maximum Output Power	500W

Package Type & Size	
Package / Mounting	Open frame
Width(W)	180mm Nom. (7.09in Nom.)
Height(H)	37mm Nom. (1.46in Nom.)
Depth(D)	102mm Nom. (4.02in Nom.)
Weight	

Other	
Operating Temp. Range	0 to 50°C
Cooling	Forced air Convection

Safety Standard(Certified)	IEC60601-1 CSA60601-1 EN60601-1 ES60601-1 UL60601-1 IEC60950-1 CSA60950-1 EN60950-1 UL60950-1
Safety Standard(Conformed)	IEC60065 CSA60065 EN60065 UL60065 IEC61010-1 EN61010-1
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.