


ZWS75BAF-3/CO2



| | |
|-------------------------------|---|
| Sales Region | Worldwide |
| Series | ZWS-BAF |
| Status | Production |
| Feature | |
| Option | With coating on both sides of PCB model |
| Option Lineup | Please refer to here. |
| Recommended EMC Filter | Please refer to here. |
| Accessories | Please refer to the catalog |



| Electrical Characteristics | |
|----------------------------|---------------|
| Input Voltage Range[AC] | 85 to 265V |
| Input Voltage Range[DC] | 120 to 370V |
| Efficiency | 78% Typ. |
| Rated Output Voltage[DC] | 3.3V |
| Output Voltage Range[DC] | 2.97 to 3.63V |
| Maximum Output Current | 15A |
| Maximum Output Power | 49.5W |

| Cases Shape & Size | |
|--------------------|------------|
| Case'□ shape | PC board |
| Width(W) | 50mm Nom. |
| Height(H) | 33mm Nom. |
| Depth(D) | 150mm Nom. |
| Weight | 230g Typ. |

| Other | |
|----------------------------|---|
| Operating Temp. Range | -10 to 70°C |
| Cooling | Convection cooling |
| Safety Standard(Certified) | UL60950-1 |
| | CSA C22.2 No.60950-1 |
| | EN60950-1 |
| Safety Standard(Conformed) | EN50178 (OV II) |
| | Den-an |
| Remarks | This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions. |

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.