

## 1-Port European-Style Insert, Unloaded Shuttered Angled Module, Icon Tab, White

MODEL NUMBER: N042E-WM1-SAT



European-style insert accepts a compatible keystone jack for terminating premise audio/video, voice or data applications.

### Features

#### European Insert Connects Your In-Wall Audio/Video, Voice or Data Cable Application

This Europe-style insert with unloaded shuttered angled module is ideal for your premise wiring applications, including home theater, VoIP phones and Ethernet. Just snap a keystone jack, including one used in HDMI, DisplayPort, RCA audio, USB and Cat5e/6/6a applications, into the plate's cutout for immediate cable connection. Compatible with Tripp Lite's N042E-WF1 gang frame, the angled module facilitates easy cable installation in tight spaces without excessive bending.

#### High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white module is shuttered to resist dust. It measures 45 x 45 millimeters and blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat. Use the icon tab to quickly identify the connected port.

### Highlights

- Ideal for home theater, VoIP or Ethernet in-wall wiring installations
- High-impact plastic construction designed to blend in with your home/office décor
- White insert measures 45 x 45 mm for a sleek, professional appearance
- Angled design allows easier installation in crowded spaces without damaging the cable

### Package Includes

N042E-WM1-SAT 1-Port Europe-Style Insert, White

## Specifications

OVERVIEW	
UPC Code	037332268914
Technology	Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB 2.0 (High Speed)
Country/Region	Europe
PHYSICAL	
Color	White
Material of Construction	SPRING: SUS304; ALL ELSE: ABS (UL94V-0)
Total Number of Ports	1

Unit Dimensions (hwd / in.)	1.772 x 1.772 x 0.335
Finish	Matte
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	14 TO 140 F (-10 to 60 C)
Storage Temperature Range	-40 TO 154.4 F (-40 to 68 C)
Operating Humidity Range	10% TO 90% RH, (NON-CONDENSING)
Storage Humidity Range	10% TO 90% RH, (NON-CONDENSING)
<b>CONNECTIONS</b>	
Number of Ports	1
Side A - Connector 1	KEYSTONE JACK CUTOUT
<b>FEATURES &amp; SPECIFICATIONS</b>	
Antibacterial	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	UL 94; UL Listed; cUL Listed
Product Compliance	RoHS; REACH
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty